

ADMIRALTY SIGNAL ESTABLISHMENT

Specification AD/CV200/Issue No.2. Dated 2.9.46. To be read in conjunction with K1001.	<u>SECURITY</u>	
	<u>Specn.</u> Restricted	<u>Valve</u> Unclassified

→ Indicates a change

<u>TYPE OF VALVE:-</u> Output or Modulator Triode.		<u>MARKING</u>		
<u>CATHODE:-</u> Directly Heated, Oxide Coated.		See K1001/4.		
<u>ENVELOPE:-</u> Glass.		<u>BASE</u>		
<u>PROTOTYPE:-</u> MZ2-200		Extra Large 4-pin Bayonet Type (EL4B). See Drawing, Page 3.		
<u>RATING</u>		<u>Note</u>		
Vf	(V)	14.0	A A A	
If approx.	(A)	2.2		
Max. Va	(kV)	2.0		
Max. Wa	(W)	250		
gm	(mA/V)	5.4		
$\mu$		16		
Ra	(ohms)	3,000		
<u>CAPACITANCES (pF.)</u> → (approx. values)				
Caf →		5.6		
Cgf →		17.0		
Cag		16.5		
		<u>DRAWING</u>		
		See K1001/AI/D1		
		<u>Dimension</u>	<u>Min.</u>	<u>Max.</u>
		A mm	-	345
		B mm	-	96
		<u>PACKING</u>		
		See K1001/7.3. <i>PACKAGING</i> <i>SEE K1005</i>		

NOTES

A. At Va = 2 kV, Ia = 110 mA.

TESTS

To be performed in addition to those applicable in K1001.

	Test Conditions				Test	Limits		No. Tested	Note
	Vf(V)	Vg(V)	Va(V)	Ia(mA)		Min.	Max.		
a	14				If (A)	1.9	2.5	100% or S	1
b	14	150 V. RMS. AC.			Ia + Ig (mA)	380	-	100%	2
c	14	-152	2000		Ia (mA)	-	12	100%	
d	14	-114	2000		Ia (mA)	52	128	100%	
e	14	-76	2000		Ia (mA)	305	485	100%	3
f	14		2000	160	Reverse Ig ( $\mu$ A)	-	25	100%	4
	Read -Ig after 5 mins.								

NOTES

1. Before testing, the valve shall be preheated with Vf = 14 V. for 5 mins.
2. Read Ia + Ig soon as Va + Vg is switched on.
3. Let Ia run as briefly as possible.
4. If the maximum reverse Ig is exceeded in test 'f', run for 5 minutes more and re-test. Max. reverse Ig after total of 10 mins. is 30  $\mu$ A.

DIMENSIONS OF EL4B BASE

CV 200

