

MINISTRY OF SUPPLY - DLRD/ERE

VALVE ELECTRONIC

CV 4035

Specification MOS/CV4035 Issue 3 Dated 11.9.56 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

<u>TYPE OF VALVE</u> - Reliable Double Triode with flexible leads <u>CATHODE</u> - Indirectly-heated <u>ENVELOPE</u> - Glass <u>PROTOTYPE</u> - CV492 - 12AX7 <u>EQUIVALENT PINNED VALVE</u> - CV4004	<u>MARKING</u> K1001/4		
	<u>BASE</u> B9A/F		
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4004 Issue 3 Dated 11.9.56	<u>DIMENSIONS</u> See K1001/A1/D11		
	<u>Dimensions (mm)</u>	<u>Min</u>	<u>Max</u>
	A. Seated height	-	49
B. Diameter	19	22.2	
D. Lead length	38	-	
<u>MOUNTING POSITION</u> Any			

TESTS

The tests required by Specification MOS/CV4004 Issue 3 Dated 11.9.56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
7.2	<u>GROUP D</u> DELETE - Base Strain	No voltages	6.5	IA			
	ADD - Lead Fragility	No voltages	6.5	IA			