

MINISTRY OF SUPPLY - DIED/RRE

VALVE ELECTRONIC

CV 4041

Specification MOS/CV4041 Issue 2 Dated 6.11.56 To be read in conjunction with K1001 BS448 & BS1409	<u>SECURITY</u>	
	<u>Specification</u>	<u>Valve</u>
	UNCLASSIFIED	UNCLASSIFIED

TYPE OF VALVE - Reliable Pulse Tetrode with flexible leads CATHODE - Indirectly-heated ENVELOPE - Glass PROTOTYPE - CV416 EQUIVALENT PINNED VALVE - CV4040	<u>MARKING</u>		
	K1001/4		
	<u>BASE</u>		
	B7G/F		
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4040, Issue 2, Dated 6.11.56	<u>DIMENSIONS</u>		
	See K1001/AI/D11		
	<u>Dimensions (mm)</u>	<u>Min</u>	<u>Max</u>
	A. Seated height	-	47.5
B. Diameter	19	19.0	
D. Lead length	38	-	
	<u>MOUNTING POSITION</u>		
	Any		

TESTS

The tests required by Specification MOS/CV4040, Issue 2, Dated 6.11.56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bcl	Limits	Units
	<u>GROUP D</u>						
	<u>DELETE -</u>						
7.2	Base Strain	No voltages	6.5	IA			
	<u>ADD -</u>						
5.12	Lead Fragility	No voltages	6.5	IA			