

Picture Tube

BI-PANEL RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS
LOW-GRID-NO.2 VOLTAGE

ALUMINIZED SCREEN
110° MAGNETIC DEFLECTION
CATHODE-DRIVE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes	5	pf
Grid No.1 to all other electrodes	6	pf
External conductive coating to anode.	{ 2500 max. 2000 min.	pf
		ma

Heater Current at 6.3 volts 450 ± 25 ma

Heater Warm-Up Time (Average) 11 seconds

Electron Gun. Type Requiring No Ion-Trap Magnet

Optical:

Phosphor (for curves, see front of this section). P4—Sulfide Type, Aluminized
 Faceplate and Protective Panel. Filterglass
 Light transmission (Approx.). 40%

Mechanical:

Weight (Approx.). 32-1/2 lbs

Overall Length. 15-7/16" ± 7/16"

Neck Length 5-3/8" ± 3/16"

Projected Area of Screen. 282 sq. in.

External Conductive Coating:

Type. Regular-Band

Contact area for grounding. Near Reference Line

For Additional Information on Coatings and Dimensions:

See *Picture-Tube Dimensional-Outlines and Bulb J187 A* sheets at front of this section

Cap Recessed Small Cavity (JEDEC No.J1-21)

Base. JEDEC No.B6-214

Basing Designation for BOTTOM VIEW. 7FA

Pin 2 - Cathode


Pin 3 - Heater

Pin 4 - Heater

Pin 5 - Grid No.1

Pin 6 - Grid No.4

Pin 7 - Grid No.2



Cap - Anode

(Grid No.3,
 Grid No.5,
 Screen,
 Collector)

C - External
 Conductive
 Coating



23JP4

Maximum and Minimum Ratings, Design-Maximum Values:

Unless otherwise specified, voltage values are positive with respect to grid No. 1

ANODE VOLTAGE	{ 22000 max. 15000 min.	volts volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value.	1100 max.	volts
Negative value.	550 max.	volts
GRID-No.2 VOLTAGE	{ 70 max. 44 min.	volts volts
CATHODE VOLTAGE:		
Negative peak value	2 max.	volts
Negative bias value	0 max.	volts
Positive bias value	100 max.	volts
Positive peak value	150 max.	volts
HEATER VOLTAGE.	{ 6.9 max. 5.7 min.	volts volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds	450 max.	volts
After equipment warm-up period.	200 max.	volts
Heater positive with respect to cathode:		
Combined AC and DC voltage.	200 max.	volts
DC component.	100 max.	volts

Typical Operating Conditions for Cathode-Drive Service:

Unless otherwise specified, voltage values are positive with respect to grid No. 1

Anode Voltage	16000	volts
Grid-No.4 Voltage	0 to 500	volts
Grid-No.2 Voltage	50	volts
Cathode Voltage for visual extinction of focused raster.	35 to 50	volts

Maximum Circuit Value:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

