



TUNG-SOL

PENTODE
MINIATURE TYPE

HEATER

ANY MOUNTING POSITION



THE 6AH6WA IS A HEATER-CATHODE TYPE, HIGH TRANSCONDUCTANCE, SHARP CUT-OFF PENTODE IN THE 7 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR USE AS A WIDE BAND OR IF AMPLIFIER IN MOBILE AND AIRCRAFT APPLICATIONS.

RATINGS

MECHANICAL

MAXIMUM IMPACT ACCELERATION (SHOCK TEST-NOTE 3)	450	G
MAXIMUM VIBRATIONAL ACCELERATION (96 HR FATIGUE TEST-NOTE #4)	2.5	G
MAXIMUM BULB TEMPERATURE	180	°C

RATINGS

AND NORMAL OPERATION

	MIL-E-1 SYMBOL	DES. MIN.	NORMAL TEST CONDITIONS (NOTE 6)	NORMAL OPERATION (NOTE 5)	DES. MAX.	MIL-E-1 UNITS
HEATER VOLTAGE (NOTE 7)	Ef:	5.7	6.3	6.3	6.9	VOLTS
PLATE VOLTAGE	Eb:	---	300	300	330	vdc
GRID #1 VOLTAGE	Ee1:	---	0	0	---	vdc
GRID #2 VOLTAGE	Ee2:	---	150	150	165	vdc
GRID #3 VOLTAGE	Ee3:	---	0	0	---	vdc
PLATE DISSIPATION	Pp:	---	---	3.0	3.3	W
GRID #2 DISSIPATION	Pg2:	---	---	0.38	0.45	W
HEATER-CATHODE VOLTAGE	Ehk:	-200	---	100	+200	V
CATHODE CURRENT	Ik:	---	---	12.5	28	mAcd
CATHODE RESISTANCE	Rk:	---	160	160	---	OHMS
PLATE CURRENT (1)	Ib(1):	---	---	10	---	mAcd
GRID #2 CURRENT	Ic2:	---	---	2.5	---	mAcd
TRANSCONDUCTANCE (1)	Sm(1):	---	---	9000	---	μMHOS
PLATE RESISTANCE	Ip:	---	---	0.5	---	MEG.

CONTINUED ON FOLLOWING PAGE

PRINTED IN U. S. A.

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS¹

TEST	AQL MIL-E-1 %	MIN.	LAL	BOG	UAL	MAX	ALD	MIL-E-1 UNITS
MEASUREMENTS ACCEPTANCE								
TESTS PART 1								
COMBINED AQL=1.0% EXCLUDING MECHANICAL AND INOPERATIVES								
HEATER CURRENT:	0.65	1f:	420	432	450	468	480	36 mA
HEATER-CATHODE LEAKAGE:								
Ehk=+100 Vdc		1hk:	---	---	---	---	15	---
Ehk=-100 Vdc	0.65	1hk:	---	---	---	---	15	μAdc
GRID CURRENT:								
Rg1= 1.0 MEG.	0.65	1c(1):	---	---	---	---	-2.0	---
PLATE CURRENT (1):	0.65	1b(1):	7.5	8.7	10.0	11.3	12.5	2.5 μAdc
PLATE CURRENT (2):								
Ec1=10.0 Vdc	0.65	1b(2):	---	---	---	---	30	---
TRANSCONDUCTANCE (1):	0.65	Sm(1):	7000	8000	9000	10000	11000	12000 μMHOS
SCREEN GRID CURRENT:	0.65	1c2:	1.5	1.9	2.5	3.1	3.5	1.4 mAdc
CONTINUITY AND SHORTS (INOPERATIVES):	0.4	---	---	---	---	---	---	---
MECHANICAL:	---	---	---	---	---	---	---	---
ENVELOPE T-5½ (6-2)								
MEASUREMENTS ACCEPTANCE								
TESTS PART 2								
INSULATION OF								
ELECTRODES: Ef=6.3V								
Eg1-ALL=-100 Vdc	2.5	Rg1- all:	100	---	---	---	---	MEG.
Ep-ALL=-300 Vdc		Rp- all:	100	---	---	---	---	MEG
PLATE CURRENT (3):								
Ec1=-5.0 Vdc	2.5	1b(3):	5	---	---	---	---	μAdc
TRANSCONDUCTANCE (2):								
Ef=5.7 (NOTE 8)	2.5	ΔEf Sm(2):	---	---	---	---	15	---
GRID EMISSION:								
Ef=7.5V; PREHEAT 5 MINUTES AT Ec1= 0 Vdc; TEST AT Ec1= =-10 Vdc	2.5	1c1(2):	---	---	---	---	-2.0	---
RF NOISE:								
Esig=35 mVac; Ck= 0.2 μf	2.5	EB:	---	---	---	---	5	VU
NOISE AND MICRO- PHONICS:								
Ef=6.3 Vac; Ebb=Ecc2= 300 Vdc; Ec1=0; Rk= 200 OHMS; Ec3 to GROUND; Rp=10,000 OHMS; Rg2=60,000 OHMS; Cg2=2 μf; Ck= 1000 μf; Ecal=300 mVac.	2.5	EB:	---	---	---	---	17	VU

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS¹ - cont'd.

TEST	AQL %	MIL-E-1 SYM-BOL	MIN	LAL	BOG	UAL	MAX.	ALD	MIL-E-1 UNITS
MEASUREMENTS ACCEPTANCE TESTS PART 2- cont'd.									
COMBINED AQL=1.0% EXCLUDING MECHANICAL AND INOPERATIVES									
CAPACITANCE		Cgp:	---	---	---	---	0.035	---	pf
CAPACITANCE (NOTE 2)	6.5	Cin:	8.0	---	10	---	12	---	pf
CAPACITANCE		Cout:	3.0	---	4.5	---	6	---	pf
LOW PRESSURE VOLTAGE BREAKDOWN:									
PRESSURE=55±5mmHg;									
VOLTAGE =500 VAC.	6.5	---	---	---	---	---	---	---	---
VIBRATION (2):									
F=25 cps; G=2.5;									
Rp=2000 OHMS; Ck=									
1000 μf	2.5	Ep:	---	---	---	---	100	---	mVac
DEGRADATION RATE ACCEPTANCE TESTS									
SHOCK:									
HAMMER ANGLE=30°;									
Ehk=+100 Vdc;									
(NOTE 3)	20	---	---	---	---	---	---	---	---
FATIGUE:									
96 HRS; G=2.5									
FIXED FREQUENCY;									
F=25 min., 60 max.									
(NOTE 4)	6.5	---	---	---	---	---	---	---	---
POST SHOCK AND FATIGUE TEST END POINTS:									
VIBRATION (2):									
F=25cps; G=2.5;									
Rp=2000 ohms; Ck=									
1000 μf	---	Ep:	---	---	---	---	200	---	mVac
HEATER-CATHODE LEAKAGE:									
Ehk=+100 Vdc		lhk:	---	---	---	---	30	---	μAdc
Ehk=-100 Vdc	---	lhk:	---	---	---	---	30	---	μAdc
CHANGE IN TRANSDUCTANCE (Δ) OF INDIVIDUAL TUBES:									
GRID CURRENT(Δ):	---	Δ _t	---	---	---	---	20	---	PERCENT
MINIATURE TUBE BASE STRAIN:	---	Sm(Δ):	---	---	---	---	-4.0	---	μAdc
GLASS STRAIN (THERMAL SHOCK)	2.5	lc ₁ :	---	---	---	---	---	---	---
ACCEPTANCE LIFE TESTS									
HEATER CYCLING LIFE TEST:									
Ei=7.5V; Eb=Ec1=									
Ec2=Ec3=0V; Ehk=+									
100 Vdc; 4min on,									
4 min. off.	1.0	---	---	---	---	---	---	---	---

CONTINUED ON FOLLOWING PAGE

PRINTED IN U. S. A.

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS¹ - cont'd.

TEST	ALLOW. DEF. per CHARAC.		AQL &	MIL-E-1 SYMBOL	MIN.	MAX.	MIL-E-1 UNITS
	1st SAMPL.	CONCL. SAMPL.					
ACCEPTANCE LIFE TESTS							
HEATER CYCLING LIFE							
TEST END POINTS:							
HEATER-CATHODE LEAKAGE:							
Ehk=+100 Vdc			---	lhk:	---	30	μAdc
Ehk=-100 Vdc			---	lhk:	---	30	μAdc
1 HOUR STABILITY LIFE TEST:							
TA=ROOM; Ehk=+135Vdc; Rg1=0.1 meg. min.			---	---	---	---	---
1 HOUR STABILITY LIFE TEST END POINTS;							
CHANGE IN TRANSCONDUCTANCE (1) OF INDIVIDUAL TUBES: (TYPICAL SAMPLE SIZE=50 TUBES)			1.0	Δ _t Sm(1):	---	10	PERCENT
100 HOUR SURVIVAL RATE LIFE TEST:							
TA=ROOM; Ehk=+135 Vdc; Rg1=0.1meg. min.			---	---	---	---	---
100 HOUR SURVIVAL RATE LIFE TEST END POINTS: (TYPICAL SAMPLE SIZE=200 TUBES)							
CONTINUITY AND SHORTS (INOPERATIVES):			0.65	---	---	---	---
TRANSCONDUCTANCE (1):			1.0	Sm(1):	6300	---	μMHOS
INTERMITTENT HIGH TEMPERATURE LIFE TEST:							
T BULB=+180°C; Ehk=+135 Vdc; Rg1=0.1meg.min.			---	---	---	---	---
500 HOUR INTERMITTENT HIGH TEMPERATURE LIFE TEST END POINTS: (TYPICAL SAMPLE SIZE=20 TUBES 1st SAMPLE; 40 TUBES 2nd SAMPLE)							
INOPERATIVES:	1	3	---	---	---	---	---
GRID CURRENT (1):	1	3	---	lc(1):	0	-2.0	μAdc
HEATER CURRENT:	1	3	---	If:	410	490	MA
CHANGE IN TRANSCONDUCTANCE (1) OF INDIVIDUAL TUBES:							
TRANSCONDUCTANCE (2): (NOTE 8)	2	5	---	Δ _{Ef} Sm(2):	---	15	PERCENT
HEATER-CATHODE LEAKAGE:							
Ehk=+100 Vdc	1	3	---	lhk:	---	20	μAdc
Ehk=-100 Vdc			---	lhk:	---	20	μAdc

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CHARACTERISTICS AND QUALITY CONTROL TESTS¹ - cont'd.

TEST ACCEPTANCE LIFE TESTS - cont'd.	ALLOWABLE DEF. PER CHARACTER.		AQL %	MIL-E-1 SYMBOL	MIN.	MAX.	MIL-E-1 UNITS
	1st SAMP.	COMB. SAMP.					
ELECTRODE INSULATION:							
g ₁ -all	2	5	---	Rg ₁ -all:	50	---	MEG.
p-all			Rp-all:	50	---	MEG.	
TRANSCONDUCTANCE							
(1) AVG. CHANGE:	---	---	---	Avg. Δ _t Sm(1):	---	15	PERCENT
TOTAL DEFECTIVES	4	8	---	---	---	---	---
1000 HOUR INTERMITTENT LIFE TEST END POINTS:							
(TYPICAL SAMPLE SIZES=							
20 TUBES 1st SAMPLE;							
40 TUBES 2nd SAMPLE)							
INOPERATIVES:	2	5	---	---	---	---	---
GRID CURRENT (1):	2	5	---	lc ₁ (1):	0	-2.0	μAdc
HEATER CURRENT:	2	5	---	lf:	410	490	MA.
CHANGE IN TRANSCONDUCTANCE (1) OF INDIVIDUAL TUBES:							
HEATER-CATHODE LEAKAGE:	2	5	---	Δ _t Sm(1):	---	20	PERCENT
LEAKAGE:							
Ehk=+100 Vdc	2	5	---	lhk:	---	20	μAdc
Ehk=-100 Vdc			lhk:	---	20	μAdc	
TOTAL DEFECTIVES:	5	10	---	---	---	---	---
500 HOUR CATHODE INTER-FACE RESISTANCE LIFE TEST:							
TA=ROOM; Ef=7.5 Vac;							
Ehk=0; g ₁ , g ₂ , g ₃ and							
P FLOATING							
500 HOUR CATHODE INTER-FACE RESISTANCE LIFE TEST END POINTS:							
(TYPICAL SAMPLE SIZE=							
20 TUBES 1st SAMPLE,							
40 TUBES 2nd SAMPLE)							
INTERFACE RESISTANCE:	1	3	---	ri:	---	25	OHMS

NOTES

1. CHARACTERISTICS, QUALITY CONTROL TEST PROCEDURES, AND INSPECTION LEVELS ARE MADE ACCORDING TO THE APPROPRIATE PARAGRAPHS OF MIL-E-1, "INSPECTION INSTRUCTIONS FOR ELECTRON TUBES" AND MIL-STD-105A.
2. WITH CYLINDRICAL SHIELD #316 CONNECTED TO CATHODE LEAD.
3. TEST CONDITIONS AND ACCEPTANCE CRITERIA PER SHOCK TEST PROCEDURES OF MIL-E-1 BASIC SPECIFICATIONS.

CONTINUED ON FOLLOWING PAGE


PRINTED IN U. S. A.



TUNG-SOL

CONTINUED FROM PRECEDING PAGE

NOTES - CONT'D.

4. TEST CONDITIONS AND ACCEPTANCE CRITERIA PER FATIGUE TEST PROCEDURES OF MIL-E-1 BASIC SPECIFICATIONS.
5. THESE NORMAL VALUES REPRESENT CONDITIONS AT WHICH CONTROL OF RELIABILITY MAY BE EXPECTED.
6. THESE NORMAL TEST CONDITIONS ARE USED FOR ALL CHARACTERISTIC TESTS UNLESS OTHERWISE STATED UNDER INDIVIDUAL TEST ITEMS.
7. FOR MOST APPLICATIONS THE PERFORMANCE WILL NOT BE ADVERSELY AFFECTED BY $\pm 10\%$ HEATER VOLTAGE VARIATION, BUT WHEN THE APPLICATION CAN PROVIDE A CLOSER CONTROL OF HEATER VOLTAGE AN IMPROVEMENT IN RELIABILITY WILL BE REALIZED.
8. CHANGE OF TRANSCONDUCTANCE FOR INDIVIDUAL TUBES FROM THAT VALUE MEASURED AT $E_f=6.3$ TO THAT VALUE MEASURED AT $E_f=5.7$ V.





PRINTED IN U. S. A.