

EDISWAN

21B12

INERT GAS FILLED THYRATRON

Directly heated
TENTATIVE

GENERAL

The 21B12 is an Inert Gas Filled Thyatron suitable for welding or motor control. It has a directly heated oxide coated cathode.

RATING

Filament Voltage	V_f	2.5 V
Filament Current	I_f	9.0 A
Maximum Peak Forward Anode Voltage		1.0 kV
Maximum Peak Inverse Anode Voltage		1.25kV
Maximum Mean Cathode Current	$I_{k(av)max}$	2.5 A
Maximum Peak Cathode Current	$i_{k(max)}$	30 A
Maximum Grid Voltage (before Conduction)	$V_g(max)$	300 V
Maximum Grid Voltage (after Conduction)	$V_g(max)$	10 V
Control Ratio		200 : 1
Maximum Striking Voltage for Conduction		70 V
Voltage Drop		12 V
Ambient Temperature Range		-55° to +75° C

DIMENSIONS

Maximum Overall Length	158 mm
Maximum Diameter	40 mm


MOUNTING POSITION—Unrestricted.

21B12

EDISWAN
21B12
INERT GAS FILLED THYRATRON
Directly heated
TENTATIVE

CAP—CT3.

BASE—UX4 (E.I.A. No. A4—10).



Viewed from free end of pins

CONNECTIONS

Pin 1	Filament	f
Pin 2	Filament Centre Tap	fct
Pin 3	Grid	g
Pin 4	Filament	f
Cap	Anode	a

December, 1960

ADVANCE DATA

Associated Electrical Industries Limited

RADIO & ELECTRONIC COMPONENTS DIVISION