

T.	Logo	Type	Pins	U_f	I_f	U_a	U_{g2}	U_{g1}	I_a	I_{g2}	S	R_i
				V(±5%)	mA	V	V	V	mA	mA	mA/V	MΩ
26 A 6	Fv-mu	amer	1	26,5	70	26,5	26,5	0 ÷ - 8	1,7	0,7	2 ÷ 0,02	0,25
						250	100	-2 ÷ -25	10,5	4	4 ÷ 0,04	1
						300	100	maximum ($P_a = 3 \text{ W}$; $P_{g2} = 0,4 \text{ W}$; $U_{f/k} = 90 \text{ V}$)				
5797 ¹⁾	F	amer	2	26,5	45	26,5	26,5	0	2,75	0,9	3,45	0,07
5905 ²⁾	F	amer	3	26,5	45	26,5	26,5	0	2,3	0,9	2,85	0,11
5907 ²⁾	F	amer	3	26,5	45	26,5	26,5	0	2,7	1,1	3	0,125
6056 ³⁾	F	amer	3	26,5	45	26,5	26,5	0	maximum			
5908 ²⁾	F	amer	4	26,5	45	26,5	26,5	0	2,3	1,8	1,75	0,03
									maximum			

1) vide * 4, a, b, c, e, f, g
 2) vide * 4, a, b, c, d, e, f, g
 3) vide * 4, a, b, c, e

