

Specification MAP/CV66/Issue 3 Dated 29.8.46. To be read in conjunction with K1001.	<u>SECURITY</u>	
	<u>Specification</u> ██████████	<u>Valve</u> ██████████

—→ Indicates a change UNCLASS. UNCLASS.

<u>TYPE OF VALVE</u> : Grounded Grid Triode <u>CATHODE</u> : Indirectly heated <u>ENVELOPE</u> : Glass-enclosed in metal shell <u>PROTOTYPE</u> : RL37			<u>MARKING</u> See K1001/4	
<u>RATING</u>		<u>Note</u>	<u>BASE</u> B9G	
Filament Voltage (V)	6.3		<u>Pin</u>	<u>Electrode</u>
Filament Current (A)	0.43			
Max. Anode Voltage (V)	250		1	Heater
Max. Anode Dissipation (W)	3.0		2	Grid
Max. Cathode Current (mA)	25		3	Grid
Mutual Conductance (mA/V)	9.0	A	4	Anode
Amplification Factor	100	A	5	Anode
Anode Impedance ( $\Omega$ )	11,100	A	6	Grid
Max. Operating Frequency (Mc/s)	300		7	Grid
			8	Cathode
			9	Heater
<u>CAPACITANCES</u> (pF)			<u>DIMENSIONS</u>	
Ca - h+c	0.09	B	See K1001/Al/D2 The groove referred to in Note 1 of the drawing may be omitted.	
Cg - h+c	9.8	B		
Cag	7.5	B		

NOTES

- At  $V_a = 250V.$ ,  $V_g = -1.5V.$ ,  $I_a = 10mA.$
- Measurements made with spigot connected to grid.
- Because of the small clearance between grid and cathode the valve should be operated if possible, in a vertical plane, it may be operated in a horizontal plane, however, provided the key of the spigot is a vertical plane.

To be performed in addition to those applicable in K1001.

Test Conditions					Test	Limits		No. Tested
						Min.	Max.	
a	See K1001/AIII				CAPACITANCES (pF)			1%  (20)
	Links to H.P.	Links to L.P.	Links to E					
	4,5	1,8,9	2,3,6,7, 10, TC1, TC2	Ca - h+c		- 0.12		
	2,3,6, 7,10	1,8,9	4,5, TC1, TC2	Cg - h+c		8.4 11.2		
	4,5	2,3,6,7, 10	1,8,9, TC1, TC2	Cag		6.4 8.6		
b	Vh	Va	Vg	Ia(mA)				100% or S
	6.3	0	0	0	Ih (A)	0.38	0.48	
c	6.3	250	-	10	Vg (V)	-1.0	-2.0	100%
d	6.3	250	-	10	gm (mA/V)	8.0	11.25	100%
e	6.3	250	-	10	$\mu$	85	115	100% or S
f	6.3	250	-	10	Reverse Ig ( $\mu$ A)	-	0.75	100%
g	6.3	30 volts R.M.S. at 50 c.p.s. applied to anode and grid strapped.			Mean cathode current (mA)	60	-	100%