

VALVE ELECTRONIC**CV103**ADMIRALTY SIGNAL AND RADAR ESTABLISHMENT

Specification AD/CV103 Issue 6 dated 1st September 1955 To be read in conjunction with K1001	<table> <tr> <th data-bbox="638 243 872 294"><u>Specification</u></th><th data-bbox="872 243 1057 294"><u>SECURITY</u> <u>Valve</u></th></tr> <tr> <td data-bbox="638 319 872 361">Unclassified</td><td data-bbox="872 319 1057 361">Unclassified</td></tr> </table>	<u>Specification</u>	<u>SECURITY</u> <u>Valve</u>	Unclassified	Unclassified
<u>Specification</u>	<u>SECURITY</u> <u>Valve</u>				
Unclassified	Unclassified				

→ Indicates a change

TYPE OF VALVE:- Crystal			<u>MARKING</u> CV103	
<u>RATINGS</u>			<u>DIMENSIONS</u> K.1001/A.1/D.8	
Max. Frequency of Operation (Mc/s)	6000			
Min. Back to Forward Resistance Ratio	8:1	A		
Max. Forward Resistance (ohms)	265	A		

NOTE

A. Measured with 1.5V source and a series resistance of 500 ohms

CV103/6/1

To be performed in addition to those applicable in K1001

	Test Conditions	Test	Limits		No. Tested	Note
			Min.	Max.		
a	The crystal shall be subjected to 3000 pulse discharges in the conducting direction (Spaced at least 200 μ secs apart) from an 18 μ F condenser at an energy level of 0.5 ergs.	<u>Resistance to Burn-out</u> The crystal shall subsequently pass the tests specified below	-	-	100%	
b		Back to forward resistance ratio	10:1	-	100%	1
c		Forward resistance (Ohms)	-	250	100%	1
d	The overall performance to be measured in the standard test gear (Pattern 65682X Performance Meter for Crystal Valves).	<u>Performance Measurement</u> db's below "standard best"	-	4.5	100%	2

NOTES

1. Measured with 1.5 Volts source and a series resistance of 500 ohms.
2. A.S.R.E. will calibrate standard crystals relative to the "standard best". Sub-standard crystals should be chosen by the manufacturer for routine checks.