

To be performed in addition to those applicable in K1001.

	Test Conditions					Test	Limits		No. Tested	Note
							Min.	Max.		
a	See K1001/A III Measurements to be made in adaptor type 38.					<u>CAPACITANCES</u> (pF)				
	Links to HP	Links to IP	Links to E.							
	3	1,2,4 5,6,8	7,9,10 TC1,TC2			C _{ae}	4.7	6.2	6	
	TC1	1,2,4 5,6,8	3,7,9,10 TC2			C _{ge}	10	12	per week	
						C _{ag}	-	0.006	T/A	
b	V _h	V _a	V _{g2}	V _{g1}	I _a (mA)					
	6.3	0	0	0		I _h (A)	0.57	0.7	100% or S	1
c	6.3	200	200	-	8	V _{g1} (V)	-1.38	-2.33	100%	1
d	6.3	200	200	-	8	I _{g2} (mA)	1.5	2.5	100% or S	1
e	6.3	200	200	-	8	Reverse I _{g1} (μA)	-	0.5	100%	1
f	6.3	200	200	1V(+)ve to value found in (c)		I _a (mA)	14.6	-	100%	1
g	6.3	200	200	-7	-	I _a (mA)	-	0.1	100%	1

NOTE

1. $V_{g3} = 0$ throughout tests.