

MINISTRY OF SUPPLY D.L.R.D.(A)/R.A.E.

Specification MOSA/CV136 Issue 6 Dated 4.12.56 To be read in conjunction with B.S.448, B.S.1409 and K.1001.	<div style="text-align: center;"><u>SECURITY</u></div> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <u>Specification</u> UNCLASSIFIED </div> <div style="width: 45%;"> <u>Valve</u> UNCLASSIFIED </div> </div>
--	--

—————→ Indicates a change

TYPE OF VALVE - Miniature H.F. Pentode				<u>MARKING</u> See K.1001/4				
CATHODE - Indirectly heated				<u>BASE</u> B.S.448/B7G.				
ENVELOPE - Glass								
<u>RATING</u> (All limiting values are absolute)				Note		<u>CONNECTIONS</u>		
Heater Voltage (V)		6.3	A	Pin	Electrode			
Heater Current (A)		0.2		1	Grid	g1		
Max. Operating Anode Voltage (V)		300		2	Cathode, Supp.	k+g3		
Max. Operating Screen Voltage (V)		275		3	Heater	h		
Max. Anode Dissipation (W)		4.75		4	Heater	h		
Max. Screen Dissipation (W)		0.8		5	Anode	a		
Max. Operating Frequency (Mc/s)		100		C	6	No connection	N L	
Max. Heater-Cathode Voltage (V)		150	E	7	Screen	g2		
Max. Grid-Screen Voltage (dc) (V)		300	B	<u>DIMENSIONS</u> See B.S.448/B.7G/2.1 Size Ref. No. 2'				
Max. Grid-Cathode Voltage (dc) (V)		100						
Max. Mean Grid Current (mA)		3.3						
Mutual Conductance (mA/V)		2.6						
Inner Amplification Factor		12.0		Dimensions		Min. Max.		
<u>CAPACITANCES (pF)</u>					A Seated height		-	47.5
C in (nom.)				4.25	D	C Diameter	16.0	19.0
C out (nom.)				6.5	D	D Overall length	-	54.5
Ca, g (max.)				0.3	D	<u>MOUNTING POSITION</u> Any		

NOTES

- A. With adequate free air circulation. Valve not screened.
- B. $V_a = V_{g2} = 250V$, $I_a = 16 \text{ mA}$, $V_g = -13.5$.
- C. Max. Frequency for 100% ratings.
- D. Measured with screen.
- E. Cathode positive or negative to heater.

To be performed in addition to those applicable in K.1001

	Test Conditions				Test	Limits		No. Tested	Note
						Min.	Max.		
a	Measured on a 1 Mc/s bridge with the valve mounted in a fully shielded holder. Valve screened.				Capacitances (pF)			6 per week	
					C in	3.5	5.0		
					C out	5.8	7.2		
					C _{a,g}	-	0.3	T.A.	
b	V _h	V _a	V _{g2}	I _a	Heater Current (A)			100% or S	
	6.3	0	0	0					
c	6.5	See K.1001/5.3 except that the test voltage shall be applied with cathode both positive and negative to heater.			Heater-Cathode Leakage Current (μA)	-	40	100%	
d	6.3	250	250	16 mA	V _{g1} (V)	-11.0	-16.0	100%	
e	6.3	250	250	16 mA	I _{g2} (mA)	1.5	3.0	100% or S	
f	6.3	250	250	16 mA	Reverse I _{g1} (μA)	-	1.0	100%	
g	6.3	250	250	16 mA	g _m (mA/V)	2.1	3.1	100%	
h	6.3	250	250	50 μA	V _{g1} (V)	-	-50	100%	
j	6.3	250	-	16 mA	Inner μ	10.0	14.0	20 per week	
		V _{g1} reduced by 1V. Reduce V _{g2} to maintain I _a = 16 mA.							
k	6.3	75V peak applied between cathode and all other electrodes strapped. See K.1001/AV.			Peak current (mA)	150	-	100%	