

CV 349

Specification MAP/CV349/Issue 3 Dated 21.7.49. To be read in conjunction with K1001, ignoring clauses:- 5.2, 5.8.	<table border="1"> <tr> <th colspan="2"><u>SECURITY</u></th></tr> <tr> <td><u>Specification</u></td><td><u>Valve</u></td></tr> <tr> <td>RESTRICTED</td><td>UNCLASSIFIED</td></tr> </table>	<u>SECURITY</u>		<u>Specification</u>	<u>Valve</u>	RESTRICTED	UNCLASSIFIED
<u>SECURITY</u>							
<u>Specification</u>	<u>Valve</u>						
RESTRICTED	UNCLASSIFIED						

→ Indicates a change

<u>TYPE OF VALVE</u> - Enclosed Triggered Spark Gap.				<u>MARKING</u> See K1001/4.	
<u>CATHODE</u> - Cold				<u>PACKING</u> See K1005	
<u>ENVELOPE</u> - Glass - unmetallised protected (See Note B)				<u>BASE</u> 3 pin Quindecim	
<u>PROTOTYPE</u> - CV.6008					
<u>RATING</u>			Note	<u>CONNECTIONS</u>	
				Pin	Electrode
Trigger Voltage	(kV)	3.2	A	1	Trigger electrode
Min. Working Voltage	(kV)	6.6	A	2 to 7	Omitted
Peak Output Power	(kW)	160	A	8	Anode
				9 to 14	Omitted
				15	No connection
				T.C.	Cathode
				<u>TOP CAP</u> See K1001/AI/D5.11	
				<u>DIMENSIONS</u> See drawing on page 4.	

NOTES

## A. Under the following conditions:-

Main Gap Voltage = 7.2 kV.

Pulse Length = 1.0  $\mu$ sec.

Repetition Frequency = 1200 per sec.

Constant current charging is used and the load and line are matched.

## B. The valve shall be provided with adequate splinter proofing.

To be performed in addition to those applicable in K.1001.

	Test Conditions	Test	Limits		No. Tested	Note
			Min.	Max.		
For the purpose of the following tests, all electrode potentials shall be measured with respect to the anode, which encloses the trigger rod.						
a	Cathode Voltage = -4.5kV. max. Trigger circuit shall be derived from an approved pulse generator supplying a positive pulse of 8.5kV. $\pm 10\%$ on open circuit, at a repetition frequency of 1,200 per sec., and with a build up time to max. voltage of 0.5-0.75 $\mu\text{sec}$ . The line shall be of 80 $\Omega$ impedance and designed for a pulse length of 1 $\mu\text{sec}$ ., and shall be charged through a choke of 180H. The external load shall be matched to the line.	A spark shall occur which also delivers power to the load circuit.			100%	1
b	Cathode Voltage = -7.2kV. Other conditions as in test clause 'a'.	Trigger Breakdown Voltage (kV)	-	5.0	100%	
c	Cathode voltage = -6.6kV. Other conditions as in test clause 'a'.	i. Jitter ( $\mu\text{sec}$ ) (Total lateral movement of the trailing edge of the monitored pulse).	-	0.2	100%	
		ii. Fluctuations of amplitude.	-	$\pm 10\%$	100%	

	Test Conditions	Test	Limits		No. Tested	Note
			Min.	Max.		
d	Cathode Voltage = -8.4kV. Other conditions as in test clause 'a'.	i. Jitter ( $\mu$ secs.) (Total lateral movement of the trailing edge of the monitored pulse).	-	0.2	100%	
		ii. Fluctuations of amplitude.	-	+10%	100%	
e	With the set-up as in test clause 'a' the cathode voltage shall be increased until unstable operation occurs.	Negative Cathode voltage at which irregular break- down (i.e. break- down not corre- lated with the trigger pulse) occurs at a rate of between 1 and 6 times per sec. (kV)	11.0	-	100% or S	←

NOTE

1. Test clause 'a' must be performed first in the test schedule.

