

MINISTRY OF SUPPLY, D.L.R.D.(A)/R.A.E.

Specification MOSA/CV394 Issue 2 Dated 9.2.55. To be read in conjunction with B.S.448, B.S.1409 & K.1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

—————→ Indicates a change

TYPE OF VALVE - Electron Beam Tuning Indicator				<u>MARKING</u> See K.1001/4.			
CATHODE - Indirectly heated							
ENVELOPE - Glass, unmetallised				<u>BASE</u> B.S.448/10.			
PROTOTYPE - EM34							
<u>RATINGS</u>				Note	<u>CONNECTIONS</u>		
					Pin	Electrode	
Heater Voltage	(V)	6.3		1	NC		
Heater Current	(A)	0.2		2	h		
Max. First Anode Voltage ($I_a = 0$)	(V)	600	A	3	a1		
Max. Operating				4	g		
First Anode Voltage	(V)	300	A	5	t		
Max. Second Anode Voltage ($I_a = 0$)	(V)	600	A	6	a2		
Max. Operating				7	h		
Second Anode Voltage	(V)	300	A	8	k		
Max. Target Anode Voltage	(V)	600	A	<u>DIMENSIONS</u> See K.1001/A1/D1.			
Max. Operating							
Target Anode Voltage	(V)	300	A	Dimensions (mm) Min. Max.			
Max. Heater-Cathode Voltage	(V)	100	B				
Max. Heater-Cathode Resistance	(K Ω)	20		A - 90 B - 28			
Max. Grid-Cathode Resistance	(M Ω)	3					
<u>NOTES</u>							
A. Absolute maximum value.							
B. Cathode positive or negative to heater.							

To be performed in addition to those applicable in K.1001.

	Test Conditions						Test	Limits		No. Tested	Note
								Min.	Max.		
a	Vh 6.3						Ih (A)	0.18	0.22	100% or S	
b	6.3	See K.1001.5.3 See K.1001.5.3 except that test voltage = 150V. (Cathode negative)					(i) Ih,k (μA) (ii) Ih,k (μA)	-	40 44	100% 100%	1
c	6.3	See K.1001.5.2.2					g,k leakage current (μA)	-	4.2	100%	
→ d	Vh	Va(b)	Vt	Va1	Va2	Vg1	(i) Ia1 (mA) (ii) Ia2 (mA) (iii) It (mA)	1.0 1.0 1.0	3.0 3.0 3.0	20 per week	3
	6.3	-	250	100	100	0					
e	6.3	250	250	-	-	-20	Width of Shadow Section of Second Anode (mm)	-	1	100%	3, 4
f	6.3	250	250	-	-	-12	Width of Shadow Section of Second Anode (mm)	1	-	100%	2,3,4
g	6.3	250	250	-	-	-7.5	Width of Shadow Section of First Anode (mm)	-	1	100%	3, 4
h	6.3	250	250	-	-	-2.75	Width of Shadow Section of First Anode (mm)	1	-	100%	3, 4
j	6.3	250	250	-	-	0	Shadow angle (degrees)	50	-	100%	3, 4

NOTES

- 1.0 megohm in series with μA-meter.
- Under this test condition the part of the target which is illuminated shall be of uniform brightness and the shadow edge shall be sharply defined and free from irregularities. These conditions shall also hold when the target voltage is reduced from 250 volts to 175 volts.
- Rg = 2.5 megohms.
- Ra1 = Ra2 = 1 megohm.

ELECTRONIC VALVE SPECIFICATIONS
SPECIFICATION MOA/CV394 ISSUE 2, DATED 9.2.55.
AMENDMENT NO. 1.

Page 2. Test Clause 'e'

In the column headed "Max. Limits" delete "1" and substitute "2.5".

Page 2. Test Clause 'f'

In the column headed "Test Conditions, Vg1 delete "-12" and substitute "-10". In the column headed "Min. Limits" delete "1" and substitute "2.5".

T.V.C. for R.A.E.

January, 1963.
(152462)