

VALVE ELECTRONIC

CV499

MINISTRY OF SUPPLY (S.R.D.E.)

Specification MOS/CV499 Issue 4 Dated:- 6.6.52. To be read in conjunction with K1001			<u>SECURITY</u> <u>Specification</u> <u>Valve</u> Unclassified Unclassified		
—————> indicates a change					
<u>TYPE OF VALVE</u> :- Beam power amplifier <u>CATHODE</u> :- Indirectly heated <u>ENVELOPE</u> :- Glass-unmetallised <u>PROTOTYPE</u> :- VX7050			<u>MARKING</u> See K1001/4 <u>PACKAGING</u> See K1005		
<u>RATING</u>		Note	<u>BASE</u> B8G		
Heater Voltage (V)	19.0	A A	Pin	Electrode	
Heater Current (A)	0.3		1	Heater	
Max. Anode Voltage (V)	600		2	Anode	
Max. Screen Voltage (V)	300		3	Screen grid	
Max. Anode Current (mA)	120		4	Cathode & Beam plates	
Max. Anode Dissipation (W)	25		5	Control grid	
Max. Screen Dissipation (W)	4.5		6	Control grid	
Mutual Conductance (mA/V)	6.0		7	Cathode & Beam plates	
Inner μ	9.0	8	Heater		
Max. Frequency for above ratings (Mc/s)	60		<u>DIMENSIONS</u> See K1001/AI/D1		
<u>CAPACITANCES</u> (pF)			Dimension	Min.	Max.
Cag	0.13		A mm.	-	93.0
Cge	12.0		B mm.	-	31.0
Cae	8.5		L mm.	70.0	78.0
<u>NOTES</u>					
A. Measured at $V_a = 300V$, $V_{g2} = 250V$, $I_a = 72 \text{ mA}$.					

TESTS

To be performed in addition to those applicable in K1001.

	Test Conditions					Test	Limits		No. Tested
							Min.	Max.	
a	See K1001/AIII					Capacitances (pF)			
	Links to H.P.	Links to L.P.	Links to E						
	2	5,6	1,3,4,7,8,9,10, TC1, TC2			(i) Cag	-	0.2	6
	2	1,3,4,7,8	5,6,9,10, TC1, TC2			(ii) Cae	-	10.0	per
	5,6	1,3,4,7,8	2,9,10, TC1, TC2			(iii) Cge	-	13.0	week
b	Vh	Va	Vg2	Vg1	Ia mA	Ih (A)	.27	.33	100%
c	19.0	-	-	-	-	Rev. Ig1 (μA) (Note 1)	-	5.0	100%
d	19.0	500	300	Ad-just	50	Vg1 (V)	-25	-40	100%
e	19.0	500	300	-	28	Ig2 (mA)	-	2.5	100%
f	19.0	500	300	-75	-	Ia cut-off (mA)	-	1.0	100%
g	19.0	300	300	300	-	Ie (Note 2) (A)	3.5	-	100%

NOTES

1. The duration of this test shall not exceed 3 minutes. After 2 minutes the reverse current to the control grid shall not exceed the value specified and shall not be rising.
2. This test shall be carried out by the application of a 2 μsec. pulse of 300 volts peak amplitude and 50 c/s. repetition frequency between the cathode and all other electrodes strapped together.