

ADMIRALTY SIGNAL & RADAR ESTABLISHMENT

Specification AD/CV993/Issue 3. Dated :- 20.4.48. To be read in conjunction with K1001, ignoring clauses :- 5.2; 5.3; 5.8.	<table border="1"> <tr> <th colspan="2" data-bbox="722 257 921 285">SECURITY</th></tr> <tr> <td data-bbox="722 285 921 314">Specification</td><td data-bbox="921 285 1100 314">Valve</td></tr> <tr> <td data-bbox="722 314 921 344">Restricted</td><td data-bbox="921 314 1100 344">Unclassified</td></tr> </table>	SECURITY		Specification	Valve	Restricted	Unclassified
SECURITY							
Specification	Valve						
Restricted	Unclassified						

→ Indicates a change

<u>TYPE OF VALVE</u> : Magnetron with pre-plumbed waveguide output.			<u>MARKING</u> See K1001/4.	
<u>CATHODE</u> : Indirectly heated, oxide coated.			<u>Additional Marking</u> :-	
<u>ENVELOPE</u> : Copper and glass.			Serial No.	
<u>PROTOTYPE</u> : First E1494, then E1542.			See also Note C.	
<u>RATING</u>			<u>DIMENSIONS AND CONNECTIONS</u> See Pages 3 and 4.	
			<u>PACKAGING</u> See K1005.	

TESTS

To be performed in addition to those applicable in K1001.

	Test Conditions		Test	Limits		No. Tested	Notes
	Vh (V)	Ia (A) (peak)		Min.	Max.		
a	3.0 AC or DC		Ih (A)	2.0	3.0	100%	
b	3.0	10.0	Va peak (kV)	12.5	17.5	100%	1,2
c	3.0	10.0	(i) Frequency (Mc/s)	9660	9740	100%	1,2 C
	A sliding slug, which in any position in the waveguide introduces a voltage S.W.R. of 1.5:1, followed by a matched termination, shall be used; it shall be used in the output waveguide near the magnetron. The freq. change which occurs as the slug is moved so as to move the S.W. pattern through at least $\lambda_g/2$ at the magnetron shall be noted.		(ii) Frequency pulling (Mc/s)	-	15		
d	3.0	10.0	Efficiency (Power out/Power in).	15%	-	100%	1,2 3
	Efficiency is to be measured by an approved method.						
e	3.0	Ia peak to be varied from 5 to 12 A. The change of frequency is to be observed.	Frequency continuity	The freq. shall vary smoothly and without discontinuity		A small %	1,2

NOTES

- The valve is to be pulse tested, according to the above table (tests 'b' to 'e'), in an approved circuit, and with the following test conditions :-
 - Recurrence frequency : 1500 pps) or other
 - Min. pulse length : 0.5 μ Sec.) approved figures.
 - Min. mark/space ratio : 1/1300
 - Pulse shape : Sensibly square.
 - Field strength : 3250 \pm 30 oersteds.
- No serious or continued flashing (internal or external) must occur during the tests.
- The apparatus used for the measurement of output power is to be checked after every 500 valves tested, or once a month (whichever is the shorter period) against the calorimetric method of measurement.

FIG. 1



