

Specification MAP/CV1035/Issue 7 Dated 20.1.49. To be read in conjunction with K1001.	<table> <tr> <th colspan="2">SECURITY</th></tr> <tr> <td>Specification</td><td>Valve</td></tr> <tr> <td>RESTRICTED</td><td>UNCLASSIFIED</td></tr> </table>	SECURITY		Specification	Valve	RESTRICTED	UNCLASSIFIED
SECURITY							
Specification	Valve						
RESTRICTED	UNCLASSIFIED						

→ Indicates a change

<u>TYPE OF VALVE</u> - Quiescent push-pull double pentode.				<u>MARKING</u> See K1001/4			
<u>CATHODE</u> - Directly heated.				<u>PACKING</u> See K1005			
<u>ENVELOPE</u> - Glass - unmetallised.							
<u>PROTOTYPE</u> - Q.P.21.							
<u>RATING</u>			Note	<u>BASE</u> B7			
				Pin	Electrode		
Filament Voltage	(V)	2.0	A	1	Control grid _a		
Filament Current	(A)	0.4		2	Control grid _b		
Max. Anode Voltage	(V)	150		3	Anode _b		
Max. Screen Voltage	(V)	150		4	Filament negative and suppressor grids.		
Mutual Conductance of each half	(mA/V)	2.3		5	Filament positive.		
Average Quiescent Anode Current	(mA)	3.5		6	Screen grids.		
Average Quiescent Screen Current	(mA)	0.9		7	Anode _a		
Output Load Resistance							
Anode I to Anode II	(Ω)	25,000		E			
Average Full Load Anode Current	(mA)	12.5		B			
Average Full Load Screen Current	(mA)	6.0	B				
<u>NOTES</u> A:- $V_a = 150$, $V_{g2} = 150$, $V_{g1} = -4.5$. B:- $V_a = 150$, $V_{g2} = 150$, $V_{g1} = -9$.				<u>DIMENSIONS</u> See K1001/AI/D1			
				Dimension		Min.	Max.
				A	(mm)	-	120
B	(mm)	-	51				

To be performed in addition to those applicable in K1001.

	Test Conditions				Test	Limits		No. Tested	Note
	Vf(V)	Va(V)	Vg2(V)	Vg1(V)		Min.	Max.		
a	2.0	0	0	0	If (A)	-	0.44	100% or S	
b	2.0	0	0	-20	Reverse Ig1 (μA)	-	0.3	100%	1
c	2.0	150	150	0 to -4.5	Ia Change (mA)	10	15	100%	1
d	2.0	150	150	-4.5	Ia (mA)	8.0	15.0	100%	1
e	2.0	150	150	-9.0	Ia (mA)	1.0	3.0	100%	1
f	2.0	150	150	-4.5	Difference in Ia for each half of valve (mA)	-	1.5	100%	
g	2.0	150	150	-4.5	Ig2 (mA)	4.0	8.0	100% or S	
h	2.0	150	150	-4.5	Reverse Ig1 (μA)	-	0.5	100%	1

NOTE

1:- Tests b, c, d, e and h are applicable to each half of the valve.