

MINISTRY OF SUPPLY D.L.R.D.(A)/R.A.E.

Specification MOSA/CV1511 Issue 5 Dated 16.4.1953 To be read in conjunction with K1001	<table border="1"> <tr> <th colspan="2">SECURITY</th></tr> <tr> <td>Specification UNCLASSIFIED</td><td>Valve UNCLASSIFIED</td></tr> </table>	SECURITY		Specification UNCLASSIFIED	Valve UNCLASSIFIED
SECURITY					
Specification UNCLASSIFIED	Valve UNCLASSIFIED				

—————> Indicates a change

TYPE OF VALVE - Cathode Ray Tube			<u>MARKING</u> See K1001/4	
TYPE OF DEFLECTION - Electrostatic. Suitable for symmetrical deflection.			<u>BASE</u> B 12 D	
BULB - Internally coated with conductive coating.			<u>CONNECTIONS</u>	
SCREEN - BYL10 or BYM25 or BYL46.				
PROTOTYPE - VCR511			Pin	Electrode
<u>RATING</u>			Note	
Heater Voltage	(V)	4.0		G
Heater Current	(A)	1.0		G
Max. Final Anode Voltage	(kV)	6.5		H
X-plate Sensitivity	(mm/V)	1000/Va3		H
Y-plate Sensitivity	(mm/V)	1000/Va3		No connection
<u>TYPICAL OPERATING CONDITIONS</u>				A2
Final Anode Voltage	(kV)	4.0		No connection
Second Anode Voltage	(V)	800		Y2
Beam Current	(μA)	20		X2
				A3
				X1
				Y1
			<u>DIMENSIONS</u> See Drawing on Page 3.	

<u>NOTES</u>	
A. A magnetic shield shall be supplied fitted to the valve, and be such as to provide adequate screening from internal magnetic field.	
B. When viewing the screen with the valve positioned such that the base spigot is uppermost, a positive voltage applied to the terminal X1 shall deflect the spot to the right, and a positive voltage applied to the terminal Y1 shall deflect the spot downwards.	

To be performed in addition to those applicable in K1001

Test Conditions					Test	Limits		No. Tested
						Min.	Max.	
	Vh	Va3 (kV)	Va2	Vg	<u>INTER-ELECTRODE CAPACITANCES</u> (pF)			
a	See K1001/5A.13				1. Each X or Y plate to all other electrodes. 2. Grid to all other electrodes 3. One X to one Y plate	- - -	20 20 5	5%(10)
b	4.0	0	0	0	Ih (A)	0.75	1.2	100%
c	4.0	4.0	Adjust for optimum focus	Adjust	-Vg (V)	1	-	100%
	Adjust Vg to give a light output of 0.01 candelas on a closed raster (through a G2 filter Type 26 (10AB/474))							
d	4.0	4.0	ditto	Adjust to out-off	(1) -Vg (V) (2) Change in value of Vg from test (c) (V)	23 -	60 25	
e	4.0	4.0	ditto	Adjust	(1) Line width (mm) (2) Va2 (V)	- 600	0.8 1200	100% 100%
	<u>DEFLECTION</u> With a sine wave time base of 10 kc/s (nominally) and a line length of 200 mm in the X and 200 mm in the Y directions successively. <u>GRID</u> The grid will be pulsed positively from out-off with amplitude equal to the value obtained in test d(2), the nominal value of pulse duration and recurrence being 100 μ secs and 100c/s respectively.							
f	4.0	4.0	Any convenient value	-60	<u>GRID INSULATION</u> 1. Leakage Current (μ A) 2. Increase in voltmeter reading	- -	6.0 100%	100%
	Recommended method K1001/5A.3.2 Resistor = 10M Ω							
g	4.0	4.0	Adjust for optimum focus.	Any convenient value.	<u>DEFLECTION SENSITIVITIES</u> 1.X.plate (mm/V) 2.Y.plate (mm/V)	750/Va3 750/Va3	1250/Va3 1250/Va3	10%(10)

Test Conditions					Test	Limits		No. Tested
						Min.	Max.	
h	Vh	Va3 (kV)	Va2	Vg	Deviation of spot from centre of screen (mm)	-	25	100%
	4.0	4.0	Adjust for optimum focus	Any convenient value				
j	4.0	4.0	ditto	ditto	<u>USEFUL SCREEN AREA</u>			
	Deflections measured from centre of screen				1.X deflection (mm)	± 105	-	100%
					2.Y deflection (mm)	± 50	-	100%
k	4.0	4.0	ditto	ditto	1.Orientation of X axis of deflection relative to 00' on drawing.	80°	100°	100%
					2.Angle between X and Y axes of deflection.	85°	95°	100%
l					The screen shall not be worse for graininess and non-uniformity than a standard tube or pattern.			
m	Test to be carried out in Test Set 331				Afterglow (secs)	15	-	

