

MINISTRY OF SUPPLY - D.L.R.D(A)/R.A.E.

Specification MOSA/CV1529 Issue 3. Dated 12.3.53. To be read in conjunction with K.1001	<table border="1"> <tr> <th colspan="2">SECURITY</th></tr> <tr> <td>Specification</td><td>Valve</td></tr> <tr> <td>UNCLASSIFIED</td><td>UNCLASSIFIED</td></tr> </table>	SECURITY		Specification	Valve	UNCLASSIFIED	UNCLASSIFIED
SECURITY							
Specification	Valve						
UNCLASSIFIED	UNCLASSIFIED						

→ Indicates a change

TYPE OF VALVE - Cathode Ray Tube			MARKING See K1001/4	
TYPE OF DEFLECTION - Electrostatic. Suitable for both symmetrical and asymmetrical deflection voltages			BASE B.12.D	
BULB - Internally coated with conductive coating			CONNECTIONS	
SCREEN - BEN 38				
PROTOTYPE - VCR.529				
RATING			Note	
Heater Voltage	(V)	4.0		
Heater Current	(A)	1.0		
Max. Final Anode Voltage	(kV)	5.0		
X-plate Sensitivity	(mm/V)	$\frac{357}{Va3}$		
Y-plate Sensitivity	(mm/V)	$\frac{780}{Va3}$		
TYPICAL OPERATING CONDITIONS				
Final Anode Voltage	(kV)	3.0		
Second Anode Voltage	(V)	500		
First Anode Voltage	(kV)	2.0		

NOTES

- A. The tube shall be adequately free from microphony.
- B. When viewing the screen with the tube positioned such that the base spigot is uppermost, a positive voltage applied to terminal X1 shall deflect the spot to the left and a positive voltage applied to the terminal Y1 shall deflect the spot upwards.
- C. The internal conductive coating shall be of such dimensions that it functions effectively but does not obscure the required useful screen area.
- D. The tube will normally be operated with A3 and the conductive coating tied, and if a manufacturer so desires, one or both of these electrodes may be strapped internally, with the connection omitted from contacts marked:- "Internal conductive coating".

To be performed in addition to those applicable in K.1001

Test Conditions						Test	Limits		No. Tested	Note
							Min.	Max.		
Vh	Va3 (kV)	Va2 (V)	Va1 (kV)	Vg (V)						
Deflection voltages shall be applied asymmetrically in all cases.										
a						<u>INTER-ELECTRODE CAPACITANCES (pF)</u> 1. Each X or Y plate to all other electrodes. 2. Grid to all other electrodes. 3. One X to one Y plate.	-	25	5% (10)	
b	4.0	0	0	0	0	Ih (A)	0.8	1.3	100%	
c	4.0	3.0	Adjust for optimum focus	2.0	Adjust to out off	-Vg (V)	40	80	100%	
d	4.0	3.0	ditto	2.0	-	(1) Vg (V) (2) Change in value of Vg from test (c) (V)	1	-	100%	
e	4.0	3.0	ditto	2.0	Adjust	(1) Line width (mm) (2) Va2 (V)	-	1.0	100%	
<u>DEFLECTION.</u> With a sine wave time base of 10 Kc/s (nominal) and a line length of 70 mm in the X and Y directions successively. The line width to be measured at the centre of the trace. <u>GRID.</u> The grid will be pulsed positively from out-off with amplitude equal to the value obtained in test d(2), the nominal value of pulse duration and recurrence being 100 μ secs and 100 c/s respectively.										
f	4.0	3.0	Any convenient value	2.0	-80	<u>GRID INSULATION</u> (1) Leakage Current (μ A) (2) Increase in voltmeter reading	-	8.0	100%	
Recommended method K.1001/5A.3.2 Resistor = 10M Ω										
g	4.0	0	0	0	0	<u>HEATER-CATHODE INSULATION</u> Leakage current (μ A)	-	200		
See K.1001/5A.3.3 except that the test voltage shall be 100 volts.										

Test Conditions						Test	Limits		No. tested	Note
							Min	Max		
	V _h (V)	V _{a3} (kV)	V _{a2} (V)	V _{a1} (V)	V _g (V)					
→ h	4.0	3.0	Adjust for optimum focus	2.0	Any convenient value	<u>DEFLECTION SENSITIVITIES</u> (1) X - plate (mm/V) (2) Y - plate (mm/V)	$\frac{300}{V_{a3}}$ $\frac{660}{V_{a3}}$	$\frac{415}{V_{a3}}$ $\frac{900}{V_{a3}}$	100% (10) 100% (10)	
→ j	4.0	3.0	ditto	2.0	ditto	Deviation of spot from centre of screen (mm)	-	6	100%	
→ k	4.0	3.0	ditto	2.0	ditto	<u>USEFUL SCREEN AREA</u> Diameter (mm)	70	-	100%	
→ l	4.0	3.0	ditto	2.0	ditto	<u>TRAPEZOIDAL DISTORTIONS</u> 1. Angles between adjacent sides. 2. Angles between opposite sides.	85° 175°	95° 185°	100% 100%	
→ m	4.0	3.0	ditto	2.0	ditto	1. Orientation of X axis of deflection relative to 00' on drawing. 2. Angle between X and Y axes of deflection.	80° 85°	100° 95°	100% 100%	

