

VALVE ELECTRONIC CV1636

GENERAL POST OFFICE: E-IN-C (S)

(P O V T 24)

Specification: G.P.O./CV 1636/Issue 1 Dated: 6. 8. 46. To be read in conjunction with K 1001	<table> <tr> <th colspan="2">SECURITY</th></tr> <tr> <td><u>Specification</u></td><td><u>Valve</u></td></tr> <tr> <td>Restricted</td><td>Restricted</td></tr> </table>	SECURITY		<u>Specification</u>	<u>Valve</u>	Restricted	Restricted
SECURITY							
<u>Specification</u>	<u>Valve</u>						
Restricted	Restricted						

—————> indicates a change

<u>TYPE OF VALVE:</u> Triode				<u>MARKING</u>		
<u>CATHODE:</u> Directly heated				See K 1001/4		
<u>ENVELOPE:</u> Unmetallised glass						
<u>PROTOTYPE</u> L S 5						
<u>RATING</u>				Note	<u>BASE</u>	
					British 4-pin (B4)	
				A	<u>CONNEXIONS</u>	
Filament current	(A)	0.82	Pin		Electrode	
Nominal filament voltage	(V)	4.5	1		Anode	
Max.anode voltage	(V)	200	2		Grid	
Amplification factor		6.0	3		Filament	
Mutual conductance	(mA/V)	2.0	A	4	Filament	
<u>CAPACITANCES (pF)</u>				<u>DIMENSIONS</u>		
C _{ag}	(max)	6.0	A	See K 1001/A1/D1		
C _{ae}	(max)	6.0		Dimension	Min	Max
C _{ge}	(max)	6.0		A (mm)	-	127
				B (mm)	-	64
This valve type is obsolete and this specification is for record purposes only.				<u>NOTE</u> A. Measured with V _a = 150, and V _g = -9		

TESTS

To be performed in addition to those applicable in K 1001

	TEST CONDITIONS			TEST	LIMITS		No. Tested	Note
					Min	Max		
(a)	See K 1001/A III			<u>CAPACITANCES (pF)</u>				
	Links to HP	Links to LP	Links to E					
	1	2	3,4,5,6,7,8 9,10, TC1, TC2	(i) Cag	-	6.0	6 per week	
	1	3, 4	2,5,6,7,8, 9,10, TC1, TC2.	(ii) Cae	-	6.0	6 per week	
	2	3. 4	1,5,6,7,8, 9,10,TC1, TC2.	(iii) Cge	-	6.0	6 per week	
(b)	Test Voltage 500 Volts D.C.			<u>INSULATION (megohms)</u> Between any two electrodes	500	-	1%	
	If (A)	Va	Vg					
(c)	0.82	-	-	Vf (V)	4.2	4.8	100%	
(d)	0.82	150	-2	Reverse Ig (μ A)	-	0.25	100%	
(e)	0.82	150	-9	Ra "x" (ohms)	5000	7000	100%	
(f)	0.78	150	-9	Ra "y" (ohms)	-	1.2"x"	100%	1
(g)	0.82	150	-9	μ	5.0	7.0	100%	
(h)	0.82	150	-30	Ia (μ A)	-	200	100%	

NOTE

1. Re-adjust If with Va = Vg = 0