

VALVE ELECTRONIC **CV 1665**GENERAL POST OFFICE: E-IN-C (S)

(POVT 89)

Specification: <b>G.P.O./CV1665/Issue 1</b>	<u>SECURITY</u>	
Dated: <b>18.11.46</b>	<u>Specification</u>	<u>Valve</u>
To be read in conjunction with K 1001	<b>Restricted</b>	<b>Restricted</b>

—→ indicates a change

<u>TYPE OF VALVE:</u> Triode				<u>MARKING</u>  See K1001/4		
<u>CATHODE:</u> Indirectly heated						
<u>ENVELOPE:</u> Unmetallised glass						
<u>PROTOTYPE</u> DH						
<u>RATING</u>			Note	<u>BASE</u> British 5-pin (B5)		
				<u>CONNEXIONS</u>		
Heater current	(A)	0.2	A	Pin	Electrode	
Nominal heater voltage	(V)	16.0		1	Anode	
Max. anode voltage	(V)	200		2	Grid	
Amplification factor		40.0		3	Heater	
Mutual conductance	(mA/V)	3.7		4	Heater	
Anode impedance	(ohms)	10,800	A	5	Cathode	
				<u>DIMENSIONS</u> See K1001/A1/D1		
				Dimension	Min.	Max.
				A (mm)	-	127
				B (mm)	-	51

This valve type is obsolete  
and this specification is for  
record purposes only.

NOTE

A. Measured with  $V_a = 100$ ,  
and  $V_g = 0$

To be performed in addition to those applicable in K1001

	TEST CONDITIONS			TEST	LIMITS		No. Tested	Note
	Ih(A)	Va	Vg		Min.	Max.		
(a)	0.25	-	-	Vh (V)	14.0	18.0	100%	
(b)	0.25	100	-2	Reverse Ig (μA)	-	1.0	100%	
(c)	0.25	100	0	Ia (mA)	5.7	10.7	100%	1
(d)	0.25	100	0	Mutual impedance (ohms)	250	330	100%	1

NOTE

1. Measured with grid connected to the cathode.