

MINISTRY OF SUPPLY (DLRD(A)/R.A.E.)VALVE ELECTRONIC

Specification MAP/CV 1872 Issue 2 Dated 14.2.52 To be read in conjunction with K1001	<table> <tr> <th colspan="2"><u>SECURITY</u></th></tr> <tr> <td><u>Specification</u> UNCLASSIFIED</td><td><u>Valve</u> UNCLASSIFIED</td></tr> </table>	<u>SECURITY</u>		<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED
<u>SECURITY</u>					
<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED				

—→ Indicates a change

TYPE OF VALVE - Dummy Load Lamp			<u>MARKING</u>	
ENVELOPE - Glass			See K1001/4	
<u>RATING</u>		Note	<u>BASE</u>	
			B4	
Resistance	(ohms)	600	<u>CONNECTIONS</u>	
Max. Power	(W)	200	Pin	Electrode
			1	No connection
			2	No connection
			3	Filament
			4	Filament
			<u>DIMENSIONS</u> (mm)	
			See K1001/AI/D1	
			Dimension A {max.} 150	
			Dimension B {max.} 80	
<u>NOTE</u>				
A. The lamp shall be suitable for use up to 20 Mc/s				
<u>TEST</u>				
To be performed in addition to those applicable in K1001				
Test Conditions	Test	<u>Limits</u>		No. Tested
		Min.	Max.	
Lamp to be run for 2 minutes (min), with an applied voltage of 230 V.min. 400 V. max., AC, RMS. Frequency = 50c/s.	Resistance (ohms)	540	660	100%