

VALVE ELECTRONIC CV2006

GENERAL POST OFFICE: E-IN-C (S)

Specification: GPO/CV 2006/Issue 1 Dated: February, 1953. To be read in conjunction with K 1001	<table> <tr> <th colspan="2"><u>SECURITY</u></th></tr> <tr> <td><u>Specification</u></td><td><u>Valve</u></td></tr> <tr> <td>Unclassified</td><td>Unclassified</td></tr> </table>	<u>SECURITY</u>		<u>Specification</u>	<u>Valve</u>	Unclassified	Unclassified
<u>SECURITY</u>							
<u>Specification</u>	<u>Valve</u>						
Unclassified	Unclassified						

_____> indicates a change

<u>TYPE OF VALVE:</u> Video Amplifier Pentode <u>CATHODE:</u> Indirectly heated <u>ENVELOPE:</u> Glass <u>PROTOTYPE</u> CV 173	<u>MARKING</u> See K1001/4
	<u>PACKING</u> See K 1005
	<u>BASE</u> B9G/B

This valve is a CV 173 selected (see note 1) with tags welded to the pins and fitted with a P.T.F.E. disc in accordance with P.O. drawing CD 713 intended for mounting in a B9G Solder-in Valveholder

(See outline Drawing on page 2)

Note. Mutual conductance 12.4 to 13.8mA/V with $V_a = 150V$, $V_{g2} = 250V$,
and $R_k = 56$ ohms

CV2006

OUTLINE DRAWING

