

GENERAL POST OFFICE: E-IN-C (S)

Specification: GPO/CV 2008/Issue 2 Dated: February, 1953. To be read in conjunction with K 1001	<table> <tr> <th colspan="2"><u>SECURITY</u></th></tr> <tr> <td><u>Specification</u></td><td><u>Valve</u></td></tr> <tr> <td>Unclassified</td><td>Unclassified</td></tr> </table>	<u>SECURITY</u>		<u>Specification</u>	<u>Valve</u>	Unclassified	Unclassified
<u>SECURITY</u>							
<u>Specification</u>	<u>Valve</u>						
Unclassified	Unclassified						

—————> indicates a change

<u>TYPE OF VALVE:</u> Low Noise RF Triode Amplifier <u>CATHODE:</u> Indirectly heated <u>ENVELOPE:</u> Glass, unmetallised <u>PROTOTYPE</u> CV 408	<u>MARKING</u> See K 1001/4 <u>PACKING</u> See K 1005
<p> This valve is a CV 408 with tags welded to the pins and fitted with PTFE, disc, in accordance with P.O. drawing CD 712 intended for mounting in a B7G Solder-in Valveholder (See outline Drawing on page 2) </p>	<u>BASE</u> B7G/B

OUTLINE DRAWING

