

VALVE ELECTRONIC

CV2025

GENERAL POST OFFICE: E-IN-C (S)

Specification: GPO/CV2025 Issue 1. Dated: November 1954 To be read in conjunction with K 1001	<table> <tr> <th colspan="2" data-bbox="644 265 890 319"><u>SECURITY</u></th></tr> <tr> <td data-bbox="644 319 890 425"><u>Specification</u> Unclassified</td><td data-bbox="890 319 1123 425"><u>Valve</u> Unclassified</td></tr> </table>	<u>SECURITY</u>		<u>Specification</u> Unclassified	<u>Valve</u> Unclassified
<u>SECURITY</u>					
<u>Specification</u> Unclassified	<u>Valve</u> Unclassified				

→ indicates a change

<u>TYPE OF VALVE:</u> Reliable miniature HF Pentode. <u>CATHODE:</u> Indirectly heated. <u>ENVELOPE:</u> Glass. <u>PROTOTYPE</u> CV 2195 Reliable.	<u>MARKING</u> See K 1001/4.1
<p>This valve is a CV 2195 Reliable with tags welded to the pins and fitted with a SRBP disc, in accordance with P.O. drawing CD 712 intended for mounting in a B 7G Solder-in-Valve holder.</p> <p>(See outline drawing on Page 2).</p>	<u>PACKING</u> See K 1005.
	<u>BASE</u> B 7 G/B.

CV2025

OUTLINE DRAWING

