

Specification MOSA/CV.2217 Issue 2 Dated 24.7.53 To be read in conjunction with K.1001	<div style="text-align: center;"><u>SECURITY</u></div> <div style="display: flex; justify-content: space-between;"> <span><u>Specification</u> UNCLASSIFIED</span> <span><u>Valve</u> UNCLASSIFIED</span> </div>
--	--

→ Indicates a change

TYPE OF VALVE - Gas-filled triode				<u>MARKING</u>			
CATHODE - Indirectly heated				See K.1001/4			
ENVELOPE - Glass-Metallised							
PROTOTYPE - 6K25							
<u>RATING</u>				Note		<u>BASE</u> See K.1001/AN/D2 M Dimension I.O (iii) applies	
						<u>CONNECTIONS</u>	
				A		Pin	Electrode
Heater Voltage (V) 6.3						1	Metallising
Heater Current (A) 1.02						2	Heater
Max. Anode Voltage (V) 400						3	Anode
Max. Peak Anode Current (mA) 500						4	No connection
Grid Control Ratio 20						5	Grid
Max. Anode-Cathode Voltage Drop (V) 70						6	No connection
						7	Heater
						8	Cathode
						<u>DIMENSIONS</u>	
				See K.1001/A1/D1			
				Dimension		Min.	Max.
				A m.m.		-	90
				B m.m.		-	32

NOTES

A. The voltage drop at 1a = 150 mA is 40V

To be performed in addition to those applicable in K.1001

	Test Conditions				Test	Limits		No. Tested	Note
						Min.	Max.		
	Before the following tests are made the valves should be pre-heated for a period of 1 minute under the following conditions:- $V_h = 6.3$ , $V_a = V_g = 0$ , 50V DC between heater and cathode, the cathode being positive.								
	$V_f$	$V_a$	$V_g$	$I_a$ (mA)				100% or S	
a	6.3	0	0	0					
b	6.3	100	-20	-	Reverse $I_g$ ( $\mu A$ )	-	1.0	100%	
c	6.3	100 through 1000 $\Omega$	Reduce $V_g$ until $I_a$ flows		Striking Bias (V)	-3.6	-5.9	100%	
d	5.5	Adjusted, Applied through not less than 100	0	100	Anode-Cathode voltage drop (V)	-	70	100%	
e	6.3	0	0	-	Heater-Cathode leakage current ( $\mu A$ )	-	15.0	100%	
Cathode 50V positive to negative heater terminal.									