

VALVE ELECTRONIC

CV 2400

GENERAL POST OFFICE: E-IN-C (S)

Specification: G.P.O./CV 2400/ISSUE 3	SECURITY	
Dated: July, 1957.	<u>Specification</u>	<u>Valve</u>
To be read in conjunction with K 1001	Unclassified	Unclassified

—→ indicates a change

<u>TYPE OF VALVE:</u> Germanium Junction Transistor P.N.P. Alloy Type.  <u>PROTOTYPE</u> CXT 2	<u>MARKING</u> CV 2400 and, if possible the Factory Code and Date Code - see K 1001/4. The collector lead shall be indicated by a white spot on the body adjacent to the lead. The emitter and base leads shall be indicated by spacing in an approved manner as shown on Page 4 of Specification CV 2389.
<u>RATINGS</u>  See Specification G.P.O./CV 2389 Issue 3 except that the average Noise Factor is 6 db.	
<u>DIMENSIONS, BODY</u>  <u>MOUNTING AND PACKAGING</u>  See Specification G.P.O./CV 2389 Issue 3.	<u>TESTS</u>  The tests required by Specification G.P.O./CV 2389 Issue 3 shall be performed with the same conditions and limits except that the maximum limit in Test k (Noise Factor) shall be 8 db.