

Specification MOS/CV4002	<u>SECURITY</u>	
Issue 5 Dated 6 March 1957	<u>Specification</u>	<u>Valve</u>
To be read in conjunction with K1001	UNCLASSIFIED	UNCLASSIFIED

—————> Indicates a change

TYPE OF VALVE - Reliable Pentode with flexible leads CATHODE - Indirectly heated ENVELOPE - Glass PROTOTYPE - CV138 EQUIVALENT PINNED VALVE - CV4014	<u>MARKING</u>		
	See K1001/4		
	<u>BASE</u>		
	B7G/F		
<u>RATING, CONNECTIONS, CAPACITANCES AND NOTES</u> See Specification MOS/CV4014, Issue 4 Dated 5.11.56	<u>DIMENSIONS</u>		
	See K1001/A1/D11		
	Dimension (mm)	Min	Max
	A Seated height	-	47.5
	B Diameter	16.0	19.0
	D Lead length	38	-
	<u>MOUNTING POSITION</u>		
	Any		

TESTS

The tests required by specification MOS/CV4014, Issue 4 dated 5.11.56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
	<u>GROUP D</u>						
	DELETE -						
7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			

Z.14235.R.

CV4002/5/1