

Specification MOA/CV4003	<u>SECURITY</u>	
Issue 4A Dated 4.9.63	<u>Specification</u>	<u>Valve</u>
To be read in conjunction with K1001, BS.448 and B.S.1409	UNCLASSIFIED	UNCLASSIFIED

Indicates a change ←

[illegible]

NOTES

- A. Centre-tapped heater; for operation on 6.3V connections should be made to pins 4 and 5 strapped together and pin 9.
- B. All limiting values are absolute.
- C. Each Section
- D. Measured at $V_a = 250V$; $V_g = -8.5V$ ($I_a = 10.5 \text{ mA}$)
- E. Measured without a metal screen.
- F. Difficulty may be encountered if this valve is operated for long periods of time with very small values of cathode current.
- G. Caution to Electronic Equipment Design Engineers: Special attention should be given to the temperature of valves to be operated in aircraft. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for Life Test are imposed on the valve, and will be reduced appreciably if absolute maximum ratings are exceeded. Both reliability and performance will be jeopardised if heater voltage is exceeded: life and reliability performance are directly related to the degree that regulation of the heater voltage is maintained at its centre-rated value.
- H. In addition to the requirements of K1001/4, the RETMA number shall be clearly and indelibly marked on the valve.
- J. This rating applies providing the following conditions are not exceeded. Pulse 800 μsecs long not more frequently than once in every 20 milliseconds. Duty ratio not more than 5%.

TESTS

To be performed in addition to those applicable in K1001
 Tests to be performed in the specified order unless otherwise agreed with the Inspection Authority

Test Conditions - unless otherwise stated.													
Vh (V) 12.6			Va(V) 250	Vg (V) -8.5	Vhk (V) 0	Note 1					Units		
K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	LIMITS					ALD		
						Min.	LAL	Bogey	UAL	Max.			
7.1	Glass Strain	No voltages	6.5	I									
5.2	GROUP A Insulation Reverse Grid Current	Note 7 Vg -all = -100V Va -all = 300V Rg = 500kohms. Max.		100% 100% 100%	Ig	100 100 -	-	-	-	-	0.5	-	Mohms. Mohms. μA
	GROUP B Heater Current Heater Cathode Leakage Current Anode Current Mutual Conductance	Combined AQL Note 3 Vhk = ± 100V	1.0 0.65 0.65 0.65 0.65	II II V2 II V2 II V2	Ih Ihk Ia gm	138 - - 6.5 1.75 -	- - - 9.0 - 2.0	150 - - - 10.5 - 2.2	- - 2 - 12.0 - 2.4	- - - 14.5 - 2.65 - 4.5	- - - - - - - -	mA μA μA mA mA/V mA/V	
	GROUP C Anode Current Anode Current Change in Mutual Conductance Reverse Grid Current	Combined AQL Vg = -25V Note 2 Vg = -18V Vh = 11.4V Note 4 Vh = 14V Rg = 500kohms Max. Note 5	6.5 2.5 2.5 2.5 2.5	I I I I I	Ia Ia Δgm Ig	- 5 - - -	- - - - -	- - - - -	- - - - -	20 - 15 - 1.5	- - - - -	μA μA % μA	

TESTS (Cont'd)

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	LIMITS					ALD	Units
						Min.	LAL	Bogey	UAL	Max.		
11.1	Group C (Cont'd) Noise and Microphony	$V_h = 12.6V$ $V_a(b) = 300V$ $V_g=0$ $R_L = 50$ kohms. Notes 3 & 6.	2.5	I	$V_a(AC)$	-	-	-	-	50	-	mV r.m.s.
	or alternatively Vibration Noise	$V_a(b) = 250V$ $R_L = 2$ kohms. Notes 3 & 9	2.5	I	$V_a(AC)$	-	-	-	-	100	-	mV r.m.s.
	Anode Current difference between sections		2.5	I	I_a	-	-	-	-	3.5	-	mA
7.2	GROUP D Base Strain Capacitances	No voltages The capacitances shall be measured on a 1 Mc/s bridge with the valve mounted in a fully screened socket. No Shield.	6.5 6.5	IA IC	C _{ag} C _{in} C _{out} C _{out} "	1.1 1.2 0.3 0.3	- - - -	1.5 1.6 0.50 0.45	- - - -	1.9 2.0 0.7 0.6	- - - -	pF pF pF pF
	Amplification Factor		6.5	IA V1	μ	15.5 -	16.2 -	17.0 -	17.8 -	18.5 -	-	mA/V mA/V
	Mutual Conductance	$V_a = 100V$; $V_g = 0$	6.5	IA V1	gm	2.25 -	- 2.60	- 3.0	- 3.4	3.75 -	1.8 0.9	

TESTS (Cont'd)

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	LIMITS				ALD	Units
						Min.	LAL	Bogey	UAL		
11.2	<u>GROUP E</u> Resonance Search	Va(b) = 250V RL = 2kohms Frequency range: 25 - 500 c/s	2.5	IC	Va AC	-	-	-	-	-	mV rms
11.3	Fatigue	Frequency = 170c/s: Min. peak Acceleration = 5g Duration = 30, 39, 30 hrs. Vh = 14V; switched 1 min. on, 3 mins. off. Va = Vg = 0		IA	f	200	-	-	-	-	c/s
11.1	<u>Post-Fatigue Tests</u> Vibration Noise	Combined AQL Va(b) = 250V RL = 2kohms. Notes 3 & 9	6.5 2.5		Va AC	-	-	-	-	150	mV rms
	Heater Cathode Leakage Current	Vhk = $\pm$ 100V Note 3	2.5		Ihk	-	-	-	-	30	μ A
	Reverse Grid Current Mutual Conductance	Rg = 500kohms. Max.	2.5 2.5		Ig gm	- 1.6	- -	- -	- -	1.5 -	μ A mA/V
11.4	Shock	Hammer angle = 30° No voltages		IA							
	<u>Post-Shock Tests</u> Vibration Noise	Combined AQL Va(b) = 250V RL = 2kohms Notes 3 & 9	6.5 2.5		Va AC	-	-	-	-	150	mV rms.

TESTS (Cont'd)

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	LIMITS				ALD	Units
						Min.	LAL	Bogey	UAL		
11.1	GROUP E (Cont'd) Heater Cathode Leakage Current	Vhk = $\pm$ 100V Note 3	2.5		Ihk	-	-	-	-		μ A
	Reverse Grid Current Mutual Conductance	Rg = 500kohms.Max	2.5 2.5		Ig gm	- 1.6	- -	- -	- -		μ A mA/V
AVL/ 5	GROUP F Life	Vhk = 175V Heater positive Rg = 500k Nom									
AVL/ 5.1	Stability Life Test Change in Mutual Conductance		1.0	I	Δ gm	-	-	-	-		%
AVL/ 5.3	Intermittent Life Test	See above									
	Life Test End-point 500 hrs. Inoperatives	Combined AQL	6.5 2.5	IA							
	Heater Cathode Leakage Current	Vhk = $\pm$ 100V	2.5		Ihk	-	-	-	-		μ A
	Reverse Grid Current	Rg = 500 k Max	2.5		Ig	-	-	-	-		μ A
	Mutual Conductance		2.5		gm	1.6	-	-	-		mA/V
	-do- Average change }				Δ gm	-	-	-	-		%
	Anode Current	Vg- all = -100V	4.0		Ia	5.5	-	-	-		mA
	Insulation	Vs- all = -300V	4.0		R	50	-	-	-		Mohms.

TESTS (Cont'd)

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits				ALD	Units
						Min.	LAL	Bogey	UAL		
	<u>GROUP F (Cont'd)</u>										
	<u>Life Test End-point</u> <u>1000 hrs.</u>	Combined AQL	10	IA							
	Inoperatives		4.0								
	Heater Cathode Leakage Current	Vhk = <u>±</u> 100V	4.0		Thk	-	-	-	-	20	µA
	Reverse Grid Current	Rg = 500k Max	4.0		Ig	-	-	-	-	0.5	µA
	Mutual Conductance		4.0		gm	1.5	-	-	-	2.65	mA/V
	Anode Current		6.5		Ia	5.0	-	-	-	14.5	mA
	Electrode Insulation	Vg -all = -100V Va -all = -300V			R R	30 30	- -	- -	- -	- -	Mohms. Mohms.
AIX/ 2.5	<u>GROUP G</u>										
Electrical re-test after 28 days holding period.			100%								
Inoperatives		0.5									
Reverse Grid Current	Rg = 500kohms.Max.	0.5		Ig	-	-	-	-	0.5	µA	

NOTES

1. Test each unit separately with the elements of the opposite section connected to the cathode of the active section.
2. Test each unit separately with the test voltages applied to the opposite section.
3. Connect the two sections in parallel. Parasitic suppression of 50 ohms. maximum is permissible.
4. The value of mutual conductance shall apply to individual valves and is expressed:-

$$\frac{(\text{gm at } 12.6) - (\text{gm at } 11.4)}{(\text{gm at } 12.6)} \times 100\%$$

5. Prior to this test the valves shall be pre-heated for five (5) minutes under the conditions specified below. Test immediately after pre-heating.

Vh(V)	Vg(V)	Rk(ohms)	Va(V)	Rg(megohm)
14.0	-8.5	0	250	0.5

6. Connect the cathode together and connect to earth through a 1.5k resistor. Grids shall also be earthed; Ck = 1000 μ F.
7. At least one of the tests in Group A shall be performed with the heater sections connected in parallel to a 6.3 volt supply.
8. Deleted
9. Alternatively, Va(b) = 250V, RL = 2k, Vg = 0, Rk = 410 ohms with the cathodes connected together, Ck = 1000 μ F.