

Specification MOS(A)/CV4009								
Similar to American Specification 5749/6BAGW								
Issue 2 Dated 6.4.56								
To be read in conjunction with BS.448 BS.1409 and K1001								
	<table border="1"> <tr> <th colspan="2"><u>SECURITY</u></th> </tr> <tr> <td><u>Specification</u></td> <td><u>Value</u></td> </tr> <tr> <td>UNCLASSIFIED</td> <td>UNCLASSIFIED</td> </tr> </table>		<u>SECURITY</u>		<u>Specification</u>	<u>Value</u>	UNCLASSIFIED	UNCLASSIFIED
<u>SECURITY</u>								
<u>Specification</u>	<u>Value</u>							
UNCLASSIFIED	UNCLASSIFIED							

TYPE OF VALVE		- Reliable Miniature Variable μ H. F. Pentode		MARKING K1001/L4			
CATHODE		- Indirectly heated		Additional Marking:- 5749/6BA6W			
ENVELOPE		- Glass					
PROTOTYPE		- CV.454					
R. E. T. M. A. DESIGNATION		- 5749/6BA6W		BASE BS.448/B7G			
RATING				Note	CONNECTIONS		
					Pin	Electrode	
Heater Voltage		(V)	6.3	C	1	g1	
Heater Current		(A)	0.3		2	g3	
Max. Heater - Cathode Voltage		(V)	± 150	A	3	h	
Max. Operating Anode Voltage		(V)	330	A	4	h	
Max. Anode Voltage ($I_a = 0$)		(V)	500	A	5	a	
Max. Anode Dissipation		(W)	3.3	A	6	g2	
Max. Operating Screen Voltage		(V)	135	A	7	k	
Max. Screen Voltage ($I_{g2} = 0$)		(V)	330	A			
Max. Screen Dissipation		(W)	0.7	A			
Mutual Conductance		(mA/V)	4.4	B	DIMENSIONS		
Max. Grid 1 - Cathode Resistance for Cathode Bias		($M\Omega$)	0.5		See BS.448/B7G/2.1		
Max. Grid 1 - Cathode Resistance Fixed Bias		($M\Omega$)	0.1		Size Ref. No. 2		
Max. Bulb Temperature		($^{\circ}C$)	165	C	Dimension (mm)	Min.	Max.
Max. Shock (short duration)		(g)	500		A seated height	-	47.5
Max. Acceleration (continuous operation)		(g)	2.5		C diameter	16.0	19.0
Inner Amplification Factor ($\mu g_1 g_2$)			24		D overall length	-	54.5
Mutual Conductance ($g_1 = -20V$)		($\mu A/V$)	40				
Anode Impedance		($M\Omega$)	1.0				
CAPACITANCES (pF)					MOUNTING POSITION		
C in (nom.)			5.5	D	Any		
C out (nom.)			5.0	D			
C _a , g ₁ (max.)			0.0035	D			
NOTES							
A. Absolute value.							
B. Measured at $V_a = 250V$, $V_{g2} = 100V$, $V_{g3} = 0$, $R_k = 68\Omega$ ($I_a = 11mA$, $I_{g2} = 4.2mA$.)							
C. <u>Caution to Electronic Equipment Design Engineers:</u> Special attention should be given to the temperature of valves to be operated in aircraft. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for life tests are imposed on the valve and will be reduced appreciably if absolute maximum ratings are exceeded. Both reliability and performance will be jeopardised if heater voltage ratings are exceeded: life and reliability performance are directly related to the degree that regulation of the heater voltage is maintained at its centre-rated value.							
D. Measured without screen.							

To be performed in addition to those applicable in K1001

Tests shall be performed in the specified order unless otherwise agreed with the Inspecting Authority

Test Conditions - unless otherwise specified													
Vh(V)		Va(V)		Vg1(V)		Vg2(V)		Vg3(V)		Rk(ohms)		Ck(μF)	
6.3		250		0		100		0		68		1000	
K1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units	
						Min.	LAL	Bogey	UAL	Max.	ALD		
11.1	Vibration	No Voltages		100%									
7.1	Glass Strain	No Voltages	2.5	I									
	<u>GROUP A</u>												
	Electrode Insulation	Vh = 6.3V. Note 8 Vg1 to all = -100V Vg2 to all = -300V Va to all = -300V		100% 100% 100%	R R R	100 100 100	- - -	- - -	- - -	- - -	- - -	MΩ MΩ MΩ	
	Reverse Grid Current	Vg1 = -1V. Note 6. Rg1 = 500kΩ max.		100%	Ig1	-	-	-	-	0.5	-	μA	
	<u>GROUP B</u>												
		Combined AQL	1.0	II									
	Heater Current		0.65	II	Ih	275	-	-	-	325	-	mA	
5.3	hk Leakage Current	Vhk = ±100V Note 1 Vhk = -100V cathode positive	0.65	II	Ihk	-	-	-	-	20	-	μA	
				V2	Ihk	Revised						μA	
	Anode Current		0.65	II	Ia	8.5	-	-	-	13.5	-	mA	
				V2	Ia	Revised						mA	
	Screen Current		0.65	II	Ig2	2.8	-	-	-	5.6	-	mA	
				V2	Ig2	Revised						mA	
	Mutual Conductance		0.65	II	gm	3.6	-	-	-	5.2	-	mA/V	
				V2	gm	Revised						mA/V	
	<u>GROUP C</u>												
		Combined AQL	6.5	I									
	Change of Mutual Conductance	Vh = 5.7V. Note 7	2.5	I	Δ gm	-	-	-	-	15	-	%	
	Mutual Conductance	Vg1 = -20V Rk = 0	2.5	I	gm	5	-	-	-	100	-	μA/V	
	Reverse Grid Current	Vh = 6.9V Va = 300V, Vg2 = 125V Vg3 = 0. Note 4	2.5	I	Ig1	-	-	-	-	1.0	-	μ A	
11.1	Vibration Noise	RL = 2kΩ. Note 2.	2.5	I	Va AC	-	-	-	-	100 25	-	mV rms	

CV4009

K1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units
						Min.	LAL	Bogey	UAL	Max.	ALD	
	<u>GROUP D</u>											
7.2	Base Strain	No voltages	6.5	IA								
5.9	Capacitances	Measured on 1 Mc/s bridge with valve mounted in a fully shielded socket. Valve not screened.	6.5	IC	C in C out Ca gl	4.4 3.5 -	- - -	5.5 5.0 -	- - -	6.6 6.5 0.0035	- - -	pF pF pF
	g3 Control	Vg1 = -4V Ia = 50 μ A	6.5	IA	-Vg3	70	-	-	-	140	-	V
	Inner Amplification Factor	Max. Grid swing = 1V	6.5	IA	μ g1g2	16	-	24	-	32	-	
	<u>GROUP E</u>											
11.2	Resonance Search	RL = 2k Ω Frequency:- 25 - 500 c/s	2.5	IC								
					Va AC	-	-	-	-	100	-	mV rms
11.3	Fatigue	Vh = 6.9V Note 3		IA								
	<u>Post Fatigue Tests</u>											
		Combined AQL	4.0									
5.3	hk Leakage Current	Vhk = \pm 100V Note 1	2.5		Ihk	-	-	-	-	30	-	μ A
	Reverse Grid Current	Vg1 = -1V Note 6 Rg1 = 500k Ω max.	2.5		Ig1	-	-	-	-	1.5	-	μ A
	Mutual Conductance		2.5		gm	3.3	-	-	-	5.2	-	mA/V
11.1	Vibration Noise	As in Group C	2.5		Va AC	-	-	-	-	4.0 4.50 4.50	-	mV
11.4	Shock	Hammer Angle = 30° No voltages		IA								
	<u>Post Shock Tests</u>											
		Combined AQL	4.0									
5.3	hk Leakage Current	Vhk = \pm 100V Note 1	2.5		Ihk	-	-	-	-	30	-	μ A
	Reverse Grid Current	Vg1 = -1V Note 6 Rg1 = 500k Ω max.	2.5		Ig1	-	-	-	-	1.5	-	μ A
	Mutual Conductance		2.5		gm	3.3	-	-	-	5.2	-	mA/V
11.1	Vibration Noise	As in Group C	2.5		Va AC	-	-	-	-	4.0 4.50 4.50	-	mV rms
	<u>GROUP F</u>											
AVI/5	Life	Rg1 = 100k Ω \pm 20% Vhk = 150V D.C. Heater positive. Note 5										

K1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units
						Min.	LAL	Bogey	UAL	Max.	ALD	
AVI/5.1	<u>Stability Life (1 hour)</u>			I								
	Change in Mutual Conductance		1.0		Δgm	-	-	-	-	$\frac{10}{5}$	-	%
AVI/5.2	<u>Survival Rate Life (100 hrs.)</u>			II								
AVI/5.6	<u>Inoperatives</u>		0.65									
AVI/5.3	<u>Intermittent Life</u>			IA								
	<u>Test Point 500 hrs.</u>	Combined AQL	6.5									
AVI/5.6	Inoperatives		2.5									
	Heater Current		2.5		Ih	275	-	-	-	325	-	mA
5.3	hk Leakage Current	Vhk = $\pm 100V$ Note 1	2.5		Ihk	-	-	-	-	40	-	μA
	Reverse Grid Current	Vg1 = -1V Note 6 Rg1 = 500k Ω	2.5		Ig1	-	-	-	-	1.5	-	μA
	Mutual Conductance		2.5		gm	3.0	-	-	-	5.2	-	mA/V
	Average Change of Mutual Conductance				Δgm	-	-	-	-	15	-	%
	Mutual Conductance	Vh = 5.7V	2.5		gm	2.5	-	-	-	5.2	-	mA/V
	Electrode Insulation	Vh = 6.3 Note 8 Vg1-all = -100V Vg2-all = -300V Va-all = -300V	4.0 4.0 4.0 4.0		R R R	50 50 50	- - -	- - -	- - -	- - -	- - -	M Ω M Ω M Ω
	<u>Test Point 1000 hrs.</u>	Combined AQL	10.0									
AVI/5.6	Inoperatives		4.0									
	Heater Current		4.0		Ih	275	-	-	-	325	-	mA
5.3	hk Leakage Current	Vhk = $\pm 100V$ Note 1	4.0		Ihk	-	-	-	-	40	-	μA
	Reverse Grid Current	Vg1 = -1V Note 6 Rg1 = 500k Ω	4.0		Ig1	-	-	-	-	2.0	-	μA
	Mutual Conductance		4.0		gm	2.7	-	-	-	5.2	-	mA/V
	Electrode Insulation	Vh = 6.3 Note 8 Vg1-all = -100V Vg2-all = -300V Va-all = -300V	6.3 4.0 4.0 4.0		R R R	30 30 30	- - -	- - -	- - -	- - -	- - -	M Ω M Ω M Ω
	<u>GROUP C</u>											
AIX/2.5	Electrical Retest after 28 days holding period			100%								
AVI/5.6	Inoperatives		0.5									
	Reverse Grid Current	Vg1 = -1V Note 6 Rg1 = 500k Ω max.	0.5		Ig1	-	-	-	-	1.0	-	μA

NOTES See Overleaf

NOTES

1. Heater positive and negative successively.
2. The valve shall be mounted so that the direction of vibration is parallel to the minor axis of the electrode structure.
Vibration frequency = any fixed frequency in the range 25 - 100 c/s.
Min. peak acceleration = $2.5g$.
The test shall be of sufficient duration to obtain a steady reading of noise output.
3. Valves shall be vibrated in each of the three required planes for not less than 30 hours (100 hours total). Heater switched 1 min. on 3 min. off. No other voltages. Min. peak acceleration = $5g$; frequency 170 ± 5 c/s. $30+30+30$
4. Adjust V_{g1} to give $I_a = 11.0$ mA. For this test the valve shall be preheated for five minutes under the test conditions. I_{g1} shall not be rising or out of limit after a total of 10 minutes.
5. For life tests V_a and V_{g2} may deviate from the specified value by ± 50 volts providing the average dissipation is within 10% of the value obtained under the specified conditions. Fixed bias may be used.
6. This is an additional bias applied relative to the negative end of the cathode resistor.
7. Change of mutual conductance is expressed

$$\frac{(gm \text{ at } 6.3V) - (gm \text{ at } 5.7V)}{(gm \text{ at } 6.3V)} \times 100\%$$

8. Heater and cathode strapped and considered as a single electrode.

SPECIFICATION CV.4009. ISSUE 2 dated 6-4-56

AMENDMENT NO. 1

- (1) GROUP B. Variables Tests. (V2 Inspection Level Tests)

Delete the figures in the LAL, Bogey, UAL and ALD columns
and insert "Record".

- (2) GROUP C. Vibration Noise.

Amend the maximum limit to 100 (from 25).

- (3) GROUP E. Post Fatigue and Post Shock Tests.

Vibration Noise.

Amend the maximum limit to 150 from 40 and 4.0
for Post Fatigue and Post Shock respectively.

November 1956
N. 50468R

T.V.C. Office
for R.A.E.

✓