

MINISTRY OF SUPPLY - DLRD/RRE

VALVE ELECTRONIC

CV4025

Specification MOS/CV4025 Issue 5 Dated 21.7.59 To be read in conjunction with K1001, BS448 and BS1409	<u>SECURITY</u>	
	<u>Specification</u> Unclassified	<u>Valve</u> Unclassified

Indicates a change

TYPE OF VALVE - Reliable Miniature VHF Double Diode			<u>MARKING</u> See K1001/4 <u>Additional Marking:- 6058</u>				
ENVELOPE	- Glass		<u>BASE</u> BS.448/B7G				
CATHODE	- Indirectly heated						
PROTOTYPE	- CV140						
RETMA No.	- 6058						
<u>RATINGS, CHARACTERISTICS, CONNECTIONS, CAPACITANCES AND NOTES.</u>  See Specification MOS/CV4007, Issue 3 dated 21.9.56  Except as follows:- Max.Peak Inverse voltage (V)			<u>DIMENSIONS</u> See BS.448/B7G/2.1 Size Ref. No.2				
			Dimensions(mm)	Min.	Max.		
			A Seated height	-	47.5		
			C Diameter	16.0	19.0		
			D Overall length	-	54.5		
			<u>MOUNTING POSITION</u>  Any				
<u>TESTS</u>  The tests required by Specification MOS/CV4007, Issue 3 dated 21.9.56 shall be performed.							

CV4025/5/1.