

Specification MOS/CV4034 Issue 3 Dated 11.9.56 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

TYPE OF VALVE	- Reliable Double Triode with flexible leads	<u>MARKING</u> K1001/4	
CATHODE	- Indirectly-heated	<u>BASE</u> B9A/F	
ENVELOPE	- Glass		
PROTOTYPE	- CV491 - 12AU7		
EQUIVALENT PINNED VALVE	- CV4003		
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u>		<u>DIMENSIONS</u>	
See Specification MCS/CV4003 Issue 4 Dated 11. 9. 56		See K1001/41/D11	
		Dimensions (mm)	Min Max
		A.Seated height	- 49
		B.Diameter	19 22.2
		D.Lead length	38 -
		<u>MOUNTING POSITION</u> Any	

TESTS

The tests required by Specification MOS/CV4003 Issue 4 Dated 11. 9. 56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits	Units
	<u>GROUP D</u>						
	DELETE -						
7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			