

Specification CV4040 ^{CV4040} <i>Am 11-1</i>	<u>SECURITY</u>	
Issue 2 Dated 6.11.56	<u>Specification</u>	<u>Valve</u>
To be read in conjunction with K1001, BS448 and BS1409	UNCLASSIFIED	UNCLASSIFIED

Indicates a change ←

TYPE OF VALVE - Reliable Pulse Tetrode			<u>MARKING</u>		
CATHODE - Indirectly-heated			See K1001/4		
ENVELOPE - Glass					
PROTOTYPE - CV416					
<u>RATING</u>			<u>BASE</u>		
All limiting values are absolute			See BS448/B7G/1.1		
			<u>CONNECTIONS</u>		

NOTES

- A. Tested at $V_a = V_{g2} = 250V$; $V_{g1} = -6.25V$ ($I_a = 6\mu A$ approx. tested under pulsed conditions).
- B. Caution to Electronic Equipment Design Engineers: Special attention should be given to the temperature of valves to be operated in aircraft. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for life test are imposed on the valve and will be reduced appreciably if absolute maximum ratings are exceeded. Both reliability and performance will be jeopardised if heater voltage ratings are exceeded: life and reliability performance are directly related to the degree that regulation of the heater voltage is maintained at its centre-rated value.

To be performed in addition to those applicable in K1001
and in the specified order unless otherwise agreed with the Inspecting Authority.

Test Conditions - unless otherwise specified												
		Vh (V)	Va (V)	Vg2 (V)	Ia (mA)							
		6.5	200	200	17.0							
K1001	Test	Test Conditions	AQL %	Insp Level	Sym- bol	Limits						Units
						Min	LAL	Bogey	UAL	Max	ALD	
7.1	Glass Strain	No voltages	6.5	I		-						
5.2	<u>GROUP A</u> Insulation	Vg1 - all = -100V Vg2 - all = -300V Va - all = -300V	100%	R		100	-	-	-	-		M  M  M 
	Reverse Grid Current	Rg1 = 500k Max	100%	Ig1	-	-	-	-	-	0.75		uA
	<u>GROUP B</u> Heater Current	Combined AQL	1.0	II	Ih	0.27	-	0.30	-	0.33		A
	Heater-cathode Leakage Current	Vhk = ± 100V	0.65	II	Ihk	-	-	-	-	10		uA
	Negative Grid Voltage		0.65	II	V2	-	-	-	2	-		uA
	Negative Grid Voltage for cut-off	Ia = 100uA	0.65	II	Vg1	8.4	-	-	-	15.8		V
	Screen Current		0.65	II	V2	-	-	12.5	14.2	-	1.8	V
	Mutual Conductance		0.65	II	Vg1	-	-	-	-	38		V
			0.65	II	Ig2	2.05	-	-	-	5.1		mA
			0.65	II	gm	2.6	-	-	-	5.0	-	mA/V
				V2		-	3.1	3.6	4.0	-	1.1	mA/V
	<u>GROUP C</u> Change in Vg2	Combined AQL Vg1 reduced by 2V, Vg2 reduced to maintain Ia = 17mA	6.5	I	ΔVg2	15	-	-	-	25		V
	Pulse Anode Current	Va = Vg2 = 300V Vg1 = - 100V Pulse amp = +100V tp = 10 to 15 usecs Duty cycle = 10.25	2.5	I	Ia (pk)	133	-	-	-	-		mA
	Vibration Noise Output	Va(b) = 250V Vg1 = -17V RL = 2k	2.5	I	Va AC	-	-	-	-	60		mV (pk-pk)
	<u>GROUP D</u> Grid Emission	Vh = 7.0V Vg1 = -38V Rg1 = 500K	6.5	IA	Ig1	-	-	-	-	-1.5		uA
	Capacitance	Measured on a 1 Mc/s bridge with the valve mounted in a fully screened socket. Shielded	6.5	IC	C out C in Ca gl	4.4 5.2 -	- - -	5.2 6.2 0.03	- - -	6.1 7.1 .05		pF pF pF
7.2	Base Strain	No voltages	6.5	IA								
11.2	<u>GROUP E</u> Resonance Search	Va(b) = 250V Vg1 = -17V RL = 2k Frequency range 25-500 c/s	2.5	IC								
	Vibration Noise Output				Va AC	-	-	-	-	Record		mV (pk-pk)
	Resonant Frequency				f	200	-	-	-	Record		c/s

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits					Units
						Min.	LAL	Bogey	UAL	Max.	
11.3	Fatigue	Vh = 6.9V switched 1 min on, 3 mins off Va = Vg2 = 0 Frequency = 170 c/s Min pk accel = 5g Duration = 30, 39, 30hrs.		IA							
	<u>Post Fatigue Tests</u>										
	Vibration Noise Output	Va(b) = 250V Vg1 = -17V RL = 2k	2.5		Va AC	-	-	-	-	100	mV (pk-pk)
	Heater-cathode	Vhk = ± 100V	2.5		Ihk	-	-	-	-	30	uA
	Leakage Current	Rg1 = 500k Max.	2.5		Igl	-	-	-	-	1.5	uA
	Reverse Grid Current		2.5		gm	2.5	-	-	-	5.0	mA/V
	Mutual Conductance										
11.4	Shock	No voltages Hammer angle = 30°		IA							
	<u>Post Shock Tests</u>										
	Vibration Noise Output	Va(b) = 250V Vg1 = -17V RL = 2k	2.5		Va AC	-	-	-	-	100	mV (pk-pk)
	Heater-cathode	Vhk = ± 100V	2.5		Ihk	-	-	-	-	30	uA
	Leakage current	Rg1 = 500k Max.	2.5		Igl	-	-	-	-	1.5	uA
	Reverse Grid Current		2.5		gm	2.5	-	-	-	5.0	mA/V
	Mutual Conductance										
AVI/5	<u>GROUP F</u> Life	Va=250V; Vg2=200V; Vhk=100V; Rg1=500k; Rk=1000									
AVI/5.1	<u>Stability Life Test</u> Change in Pulse Anode Current	Note 1	1.0	I	Ia (pk)	-	-	-	-	20	%
AVI/5.3	Intermittent Life Test										
AVI/5.6	<u>Life Test End-point</u> (500 hrs) Inoperatives Heater Current Heater-cathode Leakage Current Reverse Grid Current Pulse Anode Current do Average change Negative Grid Voltage Insulation	Vhk = ± 100V Rg1 = 500k Max Note 1 Vg1 - all = -100V Vg2 - all = -300V Va - all = -300V	6.5 2.5 2.5 2.5 2.5 2.5 2.5 4.0 4.0	IA	Ih Ihk Igl Ia(pk) ΔIa(pk) Vg1 R	0.27 - - 100 - 7.4 50 50 50	- - - - - - - - -	- - - - - - - - -	0.33 10 1.0 - 25 15.8 - - -	A uA uA mA % V M M M	

K1C01	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits						Units
						Min.	LAL	Bogey	UAL	Max.	ALD	
<u>GROUP F</u>												
A VI	<u>Life Test End-point</u>		10.0	IA								
	(1000 hrs.)		4.0									
	Inoperatives		4.0									
	Heater Current		4.0		Ih	0.27	-	-	-	0.33		A
	Leakage Current	Vhk = + 100V	4.0		Ihk	-	-	-	-	10		uA
	Reverse Grid Current	Rgl = 500k Max.	4.0		Igl	-	-	-	-	1.5		uA
	Pulse Anode Current	Note 1	4.0		Ia(pk)	90	-	-	-	-		mA
	Negative Grid Voltage		6.5		Vgl	6.6	-	-	-	15.6		V
<u>GROUP G</u>												
A IX				100%								
/2.5	Electrical re-test after											
AVI	28-day holding period											
/5.6	Inoperatives		0.5									
	Reverse Grid Current	Rgl = 500k Max	0.5		Igl	-	-	-	-	1.0		uA

NOTE

- The test conditions specified for Pulse Anode Current in Group C shall apply.

ELECTRONIC VALVE SPECIFICATIONS

SPECIFICATION MOS/CV 4040 ISSUE 2 DATED 6.11.56

AMENDMENT NO.1.

Page 1. Amend 'Specification MOS/CV4040' to read
'Specification MOA/CV4040'.

Page 2. Group B. Negative Grid Voltage

Amend the limits column to read as follows:-

Min. '8.4' (no change); LAL '11.3';
Bogey '12.5' (no change);
UAL '13.7'; Max. '15.8'; (no change);
ALD '2.7'

March, 1964.

T.V.C. for R.R.E.

(222284).