

Specification MOS/CV4056

Issue 2 Dated 23 Nov 1956

→ To be read in conjunction with K1001, BS448 and BS1409

SECURITYSpecificationValve

UNCLASSIFIED

UNCLASSIFIED

TYPE OF VALVE - Reliable Video Output
Pentode, with flexible leads

CATHODE - Indirectly-heated

ENVELOPE - Glass

PROTOTYPE - CV2127; 6CH6

EQUIVALENT PINNED VALVE - CV4055

MARKING

K1001/4

BASE

B91/F

DIMENSIONS

See K1001/41/D11

RATING, CONNECTIONS, CAPACITANCES and NOTES

See Specification MOS/CV4055, issue 2 dated 23 Nov 1956

Dimensions (mm)	Min	Max
A. Seated height	-	60.3
B. Diameter	19.0	22.2
D. Lead length	38	-

MOUNTING POSITION

Any

TESTS

The tests required by Specification MOS/CV4055, issue 2 dated 23 Nov 1956 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
	<u>GROUP D</u>						
	<u>DELETE -</u>						
→ 7.2	Base Strain	No voltages	6.5	IIA			
	<u>ADD -</u>						
5.12	Lead Fragility	No voltages	6.5	IIA			