

Specification MOS/CV4065 Issue 2 Dated 23 Nov 1956 To be read in conjunction with K1001, BS448 and BS1409	<u>SECURITY</u> <u>Specification</u> <u>Value</u> UNCLASSIFIED UNCLASSIFIED
--	---

TYPE OF VALVE	- Reliable Low Impedance Pentode with flexible leads.	<u>MARKING</u> K1001/4		
CATHODE	- Indirectly-heated	<u>BASE</u> B7G/F		
ENVELOPE	- Glass			
EQUIVALENT PINNED VALVE - CV 4062				
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4062, issue 2 dated 23 Nov 1956		<u>DIMENSIONS</u> Sec K1001/A1/D11		
		Dimensions(mm)	Min	Max
		A.Seated height	-	63.5
		B.Diameter	16	19
		D.Lead Length	38	-
		<u>MOUNTING POSITION</u> Any		

TES TS

The Tests required by specification MOS/CV4062, issue 2 dated 23 Nov 1956 shall be performed except as follows :-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits	Units
	<u>GROUP D</u> DELETE -						
7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			