

MINISTRY OF SUPPLY - DLRD(A)/RRE

VALVE ELECTRONIC

CV4079

Specification MOS(A)/CV 4079	<u>SECURITY</u>	
Issue 1. Dated 1st May, 1958	<u>Specification</u>	<u>Valve</u>
To be read in conjunction with K.1001 and BS 448	UNCLASSIFIED	UNCLASSIFIED

TYPE OF VALVE	- Reliable Low Impedance Triode	<u>MARKING</u>	
CATHODE	- Indirectly-heated	K.1001/4	
ENVELOPE	- Glass	<u>BASE</u>	
PROTOTYPE	- VX 3208	B9A	
EQUIVALENT FLEXIBLE LEAD VALVE	- CV 4038	<u>DIMENSIONS</u>	
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u>		See K1001 A1/D4	
See Specification MOS(A)/CV 4038, Issue 3, dated 6.11.56.		Dimension (mm)	Min. Max.
		L. Seated height	- 66
		B. Diameter	19 22.2
		A. Overall length	- 73
		<u>MOUNTING POSITION</u>	
		Any	

TESTS

The tests required by Specification MOS(A)/CV 4038, Issue 3, dated 6.11.56. shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits	Units
	<u>GROUP D</u>						
	DELETE -						
5.12	Lead Fragility	No voltages	6.5	IA			
	ADD -						
7.2	Base Strain	No voltages	6.5	IA			

CV4079/1/1