

Specification MOS/CV4095 Issue 1 Dated 8.1.59 To be read in conjunction with K.1001, BS448 and BS1409.				SECURITY	
				Specification Unclassified	
				Valve Unclassified	
—————> Indicates a change					
Type of Valve - Reliable R.F. Beam Tetrode Sharp Cut-Off Cathode - Directly Heated Envelope - Glass Unmetallised Prototype - VX 9186 Mod.				MARKING See K1001/4 except that the valve shall only be marked with the CV No., factory and date code.	
RATING (All limiting values are absolute)				BASE See App. 1 to CV2237 — BS 448/B5G/F	
				NOTE	
Filament Voltage	(V)	1.25			
Filament Current	(mA)	100			
Max. Anode Voltage	(V)	100		CONNECTIONS	
Max. Screen Voltage	(V)	100			
Max. Cathode Current	(mA)	7.0		PIN	
Max. Bulb Temperature	(°C)	100		ELECTRODE	
Max. Shock (Short Duration)	(g)	450			
Max. Acceleration (Continuous Operation)	(g)	5		1 a (red dot) 2 ^{g2} 3 f (-), bp ₁ 4 ^{g1} 5 f (+), bp ₂	
Typical Operating Conditions				DIMENSIONS	
Measured at V _a = V _{g2} = 45V. V _{g1} = 0 R _{g1} = 2 MΩ				See BS448/B5G/F Size Reference No. 1 See App. 1, to CV2237 —	
Anode Current	(mA)	3.0		Dimensions (millimetres)	
Screen Current	(mA)	0.9		Min.	Max.
Mutual Conductance	(mA/V)	2.0			
Capacitances (pF)				A. Overall Length	
C _{in} (nom.)		4.0		-	38.15
C _{out} (nom.)		2.75		-	7.264
C _a , g ₁ (max.)		0.05		-	9.804
				Lead Length	
				38.1	
				MOUNTING POSITION	
				ANY	

TESTS

To be performed in addition to those applicable in K.1001. Tests shall be performed in the specified order unless otherwise agreed with the Inspecting Authority.

Test conditions - unless otherwise specified								
Vf(V)	Va(V)	Vg ₂ (V)	Vg ₁ (V)	Rg ₁ (Megohms)				
1.25	45	45	0	2				
K.1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits		Units
						Min.	Max.	
7.1	Glass Strain	No Voltages	6.5	I				
	<u>GROUP A</u>							
	Electrode Insulation	Vf = 0 Vg ₁ - all = -100V Vg ₂ - all = -100V Va - all = -100V		100%	R R R	100 100 100		MΩ MΩ MΩ
	Reverse Grid Current	Rg ₁ = 500 kΩ max. Va = Vg ₂ = 55V Vg ₁ = -1.0V		100%	Ig ₁	-	0.5	μA
	Contact Potential	Vf = 1.25V Va = Vg ₂ = 0 Rg ₁ = 200kΩ		100%	Ig ₁	0.25		μA
	<u>GROUP B</u>	Combined AQL	1.0	II				
	Filament Current		0.65	II	If	88	112	mA
	Anode Current		0.65	II	Ia	1.9	4.1	mA
	Screen Grid Current		0.65	II	Ig ₂	0.5	1.3	mA
	Mutual Conductance (1)		0.65	II	gm	1.5	2.5	mA/V
	<u>GROUP C</u>	Combined AQL	6.5	I				
	Mutual Conductance (2)	Vf = 1.0V	2.5	I	gm	1.2	2.5	mA/V
	Mutual Conductance (3)	Vf = 1.0V Take reading after 15 mins.	2.5	I	gm	1.2	2.5	mA/V
	Mutual Conductance (4) Anode Resistance	Vf = 0.2V	2.5	I	gm Ra	1.1 0.2	-	mA/V MΩ
	R.F. Noise	E _{sig} = 30mVrms Ref. K.1006 (4.10.3.1)	2.5	I				

K.1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits		Units
						Min.	Max.	
5.12	<u>GROUP D</u>							
	Lead		6.5	IA				
	Fragility							
	Filament	Note 1		T.A.				
	Anode Short							
	Capacitances	Measured on a 1 Mc/s bridge with the valve mounted in a fully screened socket. No shield.	6.5	IC	C_{a-g_1} C_{in} C_{out}	3 2	0.05 5 3.5	pF pF pF
	Functional Test			T.A.		The valves shall operate satisfac- torily in W.S. A40 and A41		
11.3	<u>GROUP E</u>							
	Fatigue	Acceleration = 5g peak min. Time = 99 hours Note 2		IA				
	<u>Post Fatigue Tests</u>	Combined AQL	4.0					
	R.F. Noise	As in Group C	2.5					
11.4	Mutual Conductance (1)		2.5		gm	1.2		mA/V
	Shock	No voltages. Hammer angle 30°		IA				
	<u>Post Shock Tests</u>	Combined AQL	4.0					
	R.F. Noise	As in Group C	2.5					
	Mutual Conductance (1)		2.5		gm	1.2		mA/V
A VI/5 A VI/ 5.1	<u>GROUP F</u>							
	Life	$R_{g_1} = 5 \text{ M}\Omega$						
	<u>Stability Life Test</u>							
	Mutual Conductance (2)	$V_f = 1.0V$	1.0	I	gm	1.2		mA/V

K.1001 Ref.	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits		Units
						Min.	Max.	
A VI/ 5.3	<u>GROUP F</u> (Cont'd)							
	<u>Intermittent</u> <u>Life Test</u>							
	<u>Life Test</u> <u>End Point</u> (500hrs.)	Combined AQL	6.5	IA				
	A VI/ 5.6	Inoperatives	2.5					
	Mutual Conductance (1)		2.5		gm	1.2		mA/V
	Electrode Insulation	Vf = 0 Vg ₁ - all = -100V Vg ₂ - all = -100V Va - all = -100V	4.0		R R R	50 50 50		MΩ MΩ MΩ
	<u>Life Test</u> <u>End Point</u> (1,000hrs.)	Combined AQL	10	IA				
	A VI/ 5.6	Inoperatives	4.0					
	Mutual Conductance (1)		4.0		gm	1.2		mA/V
	Reverse Grid Current	As in Group A	4.0		Ig ₁	-	1.0	μA
A VI/ 5.6	Contact Potential	Vf = 1.25V Va = Vg ₂ = 0 Rg ₁ = 200kΩ	4.0		Ig ₁	To be recorded μA		
	Electrode Insulation	Vf = 0 Vg ₁ - all = -100V Vg ₂ - all = -100V Va - all = -100V	6.5		R R R	30 30 30		MΩ MΩ MΩ
A IX/ 2.4 and 2.5	<u>GROUP G</u>							
	Electrical retest after 28 days holding period			100%				
	A VI/ 5.6	Inoperatives	0.5					
	Mutual Conductance (1)				gm	1.5	2.5	mA/V
A VI/ 5.6	Reverse Grid Current	As in Group A	0.5		Ig ₁	-	0.5	μA

NOTES

CV4095

1. Raise V_f until filament opens. Test for filament to anode short only. After performance of the filament burn out test, if the short circuit shall pass in excess of five times the rated filament current without burning out the short circuit, the valve shall be deemed a failure. This test shall be performed by a Service Laboratory on three valves which shall be in addition to the required number for Type Approval samples. Manufacturers' data are not required for this test.
2. Filament voltage and H.T. voltages switched simultaneously 1 min. on and 3 min. off throughout duration of test. Frequency = 170 cps. The valves to be vibrated in each of three mutually perpendicular planes in turn for periods of 30, 30 and 39 hours. One plane to include the longitudinal axis of the valve.

SPECIFICATION CV.4095

ISSUE 1 DATED 8.1.59

AMENDMENT No. 1

Page 2 GROUP C

Immediately following the test for "Mutual Conductance (3)"

Add new test as follows:-

<u>Test</u>	<u>Test</u> <u>Conditions</u>	<u>AQL</u> <u>%</u>	<u>Insp.</u> <u>Level</u>	<u>Sym-</u> <u>bol</u>	<u>Limits</u>		<u>Units</u>
					<u>Min.</u>	<u>Max.</u>	
Mutual Conductance (4)	Vf = 0.8V	2.5	I	gm	1.1	-	mA/V

April, 1959.
N.54789/D.

T.V.C. for S.R.D.E.

✓
HHS
9.759

ELECTRONIC VALVE SPECIFICATIONS

SPECIFICATION MOS/CV4095

ISSUE NO.1 DATED 8.1.59.

AMENDMENT NO.2

On Page 4, under GROUP F
(Cont'd)
Intermittent
Life Test

(1) Delete Life Test
End Point
(500 hours)

(2) Immediately following the above, in
column headed "Test"

Amend Life Test to read Life Test
End Point End Point
(1,000 hours) (500 hours)

TVC for SRDE

August, 1959.

N.71076/D

✓ HAK

ELECTRONIC VALVE SPECIFICATION

CV4095 Issue 1 Dated 8.1.59
AMENDMENT No. 3

Page 1 Base

Delete:- See Appendix 1 to CV2237

Dimensions

Delete:- See Appendix 1 to CV2237

Signals Radio Development
Establishment

December 1961

(7730)

25.2.62
[Signature]