

MINISTRY OF SUPPLY - DLRD/RRE

VALVE ELECTRONIC CV4098

Specification MOS/CV 4098 Issue 1 Dated 14.7.59 To be read in conjunction with K1001, K1006, BS448 and BS1409	<u>SECURITY</u> <u>Specification</u> <u>Valve</u> Unclassified Unclassified
--	--

Indicates a change

TYPE OF VALVE - Reliable RF Pentode, Flying Lead ENVELOPE - Glass CATHODE - Indirectly heated PROTOTYPE - CV4011, 5725/6AS6W	<u>MARKING</u> K1001/4 <u>BASE</u> BS448: B7G/F/1.1
<u>RATINGS AND CHARACTERISTICS</u> See Specification MOS/CV4011 Issue 2 dated 26.2.57	<u>DIMENSIONS</u> BS.448: B7G/F/2.1/1 <u>Dimensions (Ins) Min. Max.</u> A. Seated height 1½ C. Diameter 0.666 0.733 E. Lead length 1.5 <u>MOUNTING POSITION</u> Any

TESTS

The tests required by specification MOS/CV4011, Issue 2, dated 26.2.57 shall be performed except as follows:-

K1001	TEST	TEST CONDITIONS	AQL %	Insp. Level	Sym- bol	LIMITS			UNITS
						Min	Bogey	Max.	
5.12	DELETE. On page 2. under <u>Degradation</u> <u>Rate Acceptance</u> <u>Tests.</u> Clause 4.9.6.1 Base Strain ADD Lead Fragility	No Voltages	6.5	IA					

CV4098/1/1.

Z.19678.