

CV5068

Page 2

TESTS

To be performed in addition to those applicable in K 1001

Test Conditions					Test	Limits		No. Tested	Note
	Vf (Vac)	Va (V)	Vg (V)	Ia (mA)		Min	Max		
a	10.0				If (A)	4.0	4.8	100%	
b	10.0	1000		75	Reverse Ig (μA)	-	10	100%	
c	10.0	1000	-70		Ia (mA)	65	-	100%	
d	10.0	1000	-60		Ia (mA)	105	-	100%	
e	10.0	1000	-55		Ia (mA)	130	-	100%	
f	10.0	1000	-50		Ia (mA)	155	-	100%	
g	10.0	Grid and anode strapped Peak applied volts = 2000 See K 1001/A.V.			Ie (A)	3	-	100%	

Amendment No. 1

To issue 1 dated July, 1957

of Specification Valve Electronic CV.5068

Page 1

At middle of page, on right hand side, in tabulation under heading of CONNEXIONS,

Amend entries for electrodes against Pins 1, 2 and 3 to the following:-

<u>Pin</u>	<u>Electrode</u>
1	Grid
2	Filament
3	Anode

(Note: the electrode entry against Pin 4 remains as originally printed).

May, 1958.

T.V.C. for G.P.O.

N. 25476/R