

## Picture Tube

RECTANGULAR GLASS TYPE  
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN  
90° MAGNETIC DEFLECTION

### GENERAL DATA

#### Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes. . . . .	5	pf
Grid No.1 to all other electrodes. . . . .	6	pf
External conductive coating to anode . . . . .	{ 1500 max.	pf
	{ 1000 min.	pf
Heater Current at 6.3 volts. . . . .	600 ± 30	ma
Electron Gun . . . . .	Type Requiring No Ion-Trap Magnet	

#### Optical:

Phosphor (For curves, see front of this section) .P4—Sulfide Type, Aluminized	
Faceplate, Spherical . . . . .	Filterglass
Light transmission (Approx.) . . . . .	74%

#### Mechanical:

Weight (Approx.) . . . . .	15 lbs
Overall Length . . . . .	14-5/8" ± 3/8"
Neck Length. . . . .	5-1/2" ± 3/16"
Projected Area of Screen . . . . .	149 sq. in.

External Conductive Coating:

Type . . . . .	Regular-Band
Contact area for grounding . . . . .	Near Reference Line

For Additional Information on Coatings and Dimensions:

See *Picture-Tube Dimensional-Outlines and Bulb J133 F/G* sheets at front of this section

Cap. . . . . Recessed Small Cavity (JEDEC No.J1-21)


Bases (Alternates):

Small-Shell Duodecal 6-Pin (JEDEC Group 4, No.B6-63)

Short Small-Shell Duodecal 6-Pin (JEDEC No.B6-203)

Basing Designation for BOTTOM VIEW . . . . . 12L

- Pin 1—Heater
- Pin 2—Grid No.1
- Pin 6—Grid No.4
- Pin 10—Grid No.2
- Pin 11—Cathode
- Pin 12—Heater



- Cap—Anode  
(Grid No.3,  
Grid No.5,  
Screen,  
Collector)
- C—External  
Conductive  
Coating

← indicates a change.



# 17BJP4

## → Maximum and Minimum Ratings, Design-Maximum Values:

*Unless otherwise specified, voltage values are positive with respect to cathode*

ANODE VOLTAGE. . . . .	{17500 max.	volts
	{11000 min.	volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value . . . . .	1100 max.	volts
Negative value . . . . .	550 max.	volts
GRID-No.2 VOLTAGE. . . . .	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value. . . . .	220 max.	volts
Negative bias value. . . . .	155 max.	volts
Positive bias value. . . . .	0 max.	volts
Positive peak value. . . . .	2 max.	volts
HEATER VOLTAGE . . . . .	{6.9 max.	volts
	{5.7 min.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds . . . . .	450 max.	volts
After equipment warm-up period . . . . .	200 max.	volts
Heater positive with respect to cathode:		
Combined AC and DC voltage . . . . .	200 max.	volts
DC component . . . . .	100 max.	volts

## Typical Operating Conditions for Grid-Drive Service:

*Unless otherwise specified, voltage values are positive with respect to cathode*

Anode Voltage. . . . .	14000	volts
Grid-No.4 Voltage. . . . .	-55 to +300	volts
Grid-No.2 Voltage. . . . .	300	volts
Grid-No.1 Voltage for visual extinction of focused raster . . . . .	-28 to -72	volts

## Maximum Circuit Value:

Grid-No.1-Circuit Resistance . . . . .	1.5 max.	megohms
----------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet  
*X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES*  
at front of this Section

→ Indicates a change.

