

17GJ5A

Beam Power Tube

NOVAR TYPE

The 17GJ5A is the same as the 6GJ5A except for:

Heater Characteristics and Ratings

| | |
|-------------------------------------|-----------------|
| Current | 0.450 ± 0.030 A |
| Voltage (AC or DC) at 0.450 A | 16.8 V |
| Warm-up time (Average) | 11 s |

17GW6/17DQ6B

Beam Power Tube

NOVAR TYPE

The 17GW6/17DQ6B is the same as the 6GW6 except for:

Heater Characteristics and Ratings

| | |
|-------------------------------------|-----------------|
| Current | 0.450 ± 0.030 A |
| Voltage (AC or DC) at 0.450 A | 16.8 V |
| Warm-up time (Average) | 11 s |

17JB6A

Beam Power Tube

NOVAR TYPE

The 17JB6A is the same as the 6JB6A except for:

Heater Characteristics and Ratings

| | |
|-------------------------------------|-----------------|
| Current | 0.450 ± 0.030 A |
| Voltage (AC or DC) at 0.450 A | 16.8 V |
| Warm-up time (Average) | 11 s |



Electronic
Components

DATA
8-70

17JF6

Beam Power Tube

NOVAR TYPE

The 17JF6 is the same as the 6JF6 except for:

Heater Characteristics and Ratings

| | |
|-------------------------------------|-----------------|
| Current | 0.600 ± 0.040 A |
| Voltage (AC or DC) at 0.600 A | 16.8 V |
| Warm-up time (Average) | 11 s |

17JG6A

Beam Power Tube

NOVAR TYPE

The 17JG6A is the same as the 6JG6A except for:

Heater Characteristics and Ratings

| | |
|-------------------------------------|-----------------|
| Current | 0.600 ± 0.040 A |
| Voltage (AC or DC) at 0.600 A | 16.8 V |
| Warm-up time (Average) | 11 s |