

Beam Power Tube With an Integral Diode

The 17JQ6 is the same as the 6JQ6 except for:

Heater Characteristics and Ratings

Current	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A	17.0	V
Warm-up time (Average)	11	s

17JR6

Beam Power Tube

Novar Type

The 17JR6 is the same as the 6JR6 except for:

Heater Characteristics and Ratings

Current	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600 A	16.8	V
Warm-up time (Average)	11	s

17JT6A

Beam Power Tube

Novar Type

The 17JT6A is the same as the 6JT6A except for:

Heater Characteristics and Ratings

Current	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A	16.8	V
Warm-up time (Average)	11	s

17JZ8

Medium-Mu Triode— Beam Power Tube

Duodecar Type

The 17JZ8 is the same as the 6JZ8 except for:

Heater Characteristics and Ratings

Current	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A	16.8	V
Warm-up time (Average)	11	s

17KV6

Beam Power Tube

Novar Type

The 17KV6 is the same as the 6KV6 except for:

Heater Characteristics and Ratings

Current	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600A	16.8	V
Warm-up time (Average)	11	s

17KV6A

Beam Power Tube

Novar Type

The 17KV6A is the same as the 6KV6A except for:

Heater Characteristics and Ratings

Current	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600A	16.8	V
Warm-up time (Average)	11	s