

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3BC5 is the same as the 6BC5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average)	11	sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200	max. volts
Heater positive with respect to cathode	200 [▲]	max. volts

3BN4

Medium-Mu Triode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3BN4 is the same as the 6BN4 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3	volts
Current	0.45 ± 6%	amp
Warm-up time (Average)	11	sec

3BN6

Beam Tube

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 3BN6 is the same as the 6BN6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average)	11	sec

[▲] The dc component must not exceed 100 volts.



3BU8

Sharp-Cutoff Twin Pentode

With Common Cathode, Grid No.1, and Grid No.2

9-PIN MINIATURE TYPE

For Equipment Having Series
Heater-String Arrangement

The 3BU8 is the same as the 6BU8 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average)	11	sec

3BY6

Pentagrid Amplifier

7-PIN MINIATURE TYPE

For Equipment Having Series
Heater-String Arrangement

The 3BY6 is the same as the 6BY6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average)	11	sec

3BZ6

Semiremote-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series
Heater-String Arrangement

The 3BZ6 is the same as the 6BZ6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	3.15	volts
Current	0.6 ± 6%	amp
Warm-up time (Average)	11	sec

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode .	300 [▲] max.	volts
Heater positive with respect to cathode .	200 [●] max.	volts

[▲] The dc component must not exceed 200 volts.

[●] The dc component must not exceed 100 volts.

