

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 4DT6 is the same as the 6DT6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.2	volts
Current	0.45 ± 6%	amp
Warm-up time (Average).	11	sec

4DT6

Sharp-Cutoff Pentode

With Two Independent Control Grids

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 4DT6 is the same as the 6DT6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.2	volts
Current	0.45 ± 6%	amp
Warm-up time (Average).	11	sec

4DT6-A

Sharp-Cutoff Pentode

With Two Independent Control Grids

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 4DT6-A is the same as the 6DT6-A except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.2	volts
Current	0.45 ± 6%	amp
Warm-up time (Average).	11	sec



4EW6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 4EW6 is the same as the 6EW6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	4.2	volts
Current	0.6 ± 6%	amp
Warm-up time (Average).	11	sec

