

# 8AW8A

## High-Mu Triode— Sharp-Cutoff Pentode

### 9-PIN MINIATURE TYPE

*The 8AW8A is the same as the 6AW8A except for the following items:*

Heater Characteristics and Ratings:

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	8.4	volts
Warm-up time (Average). . . . .	11	sec

# 8B10

## Twin Diode— Medium-Mu-Twin Triode

### DUODECAR TYPE

*The 8B10 is the same as the 6B10 except for the following items:*

Heater Characteristics and Ratings:

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	8.5	volts
Warm-up time (Average). . . . .	11	sec

# 8BA8A

## Medium-Mu Triode— Sharp-Cutoff Pentode

### 9-PIN MINIATURE TYPE

*The 8BA8A is the same as the 6BA8A except for the following items:*

Heater Characteristics and Ratings:

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	8.4	volts
Warm-up time (Average). . . . .	11	sec



# 8BH8

## Medium-Mu Triode— Sharp-Cutoff Pentode

### 9-PIN MINIATURE TYPE

*The 8BH8 is the same as the 6BH8 except for the following items:*

Heater Characteristics and Ratings:

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	8.4	volts
Warm-up time (Average). . . . .	11	sec

# 8BN8

## Twin Diode—High-Mu Triode

### 9-PIN MINIATURE TYPE

*The 8BN8 is the same as the 6BN8 except for the following items:*

Heater Characteristics and Ratings:

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	8.4	volts
Warm-up time (Average). . . . .	11	sec

# 8BQ5

## Power Pentode

### 9-PIN MINIATURE TYPE

*The 8BQ5 is the same as the 6BQ5 except for the following items:*

Heater Characteristics and Ratings:

Current . . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	8.0	volts
Warm-up time (Average). . . . .	11	sec





8AU8  
TO  
8BH8

## 8AU8

### MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 8AU8 is the same as the 6AU8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	8.4	volts
Current . . . . .	0.45	amp

## 8AW8-A

### HIGH-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 8AW8-A is the same as the 6AW8-A except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	8.4	volts
Current . . . . .	0.45	amp

## 8BH8

### MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 8BH8 is the same as the 6BH8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	8.4	volts
Current . . . . .	0.45	amp

8BN8  
TO  
8CG7



## 8BN8

### TWIN DIODE-HIGH-MU TRIODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 8BN8 is the same as the 6BN8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	8.4	volts
Current . . . . .	0.45 ± 6%	amp

## 8BQ5

### POWER PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 8BQ5 is the same as the 6BQ5 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	8	volts
Current . . . . .	0.6	amp
Warm-up time (Average) . . . . .	11	sec

## 8CG7

### MEDIUM-MU TWIN TRIODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having  
series heater-string arrangement*

*The 8CG7 is the same as the 6CG7 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	8.4	volts
Current . . . . .	0.45	amp