


TUNG-SOL

BEAM PENTODE


6L6




METAL SHELL

COATED UNIPOTENTIAL CATHODE
 HEATER
 6.3 VOLTS 0.9 AMP.
 AC OR DC
 ANY MOUNTING POSITION


6L6G



GLASS BULB



BOTTOM VIEW
 SMALL WAFER
 7 PIN OCTAL
 7AC



BOTTOM VIEW
 MEDIUM SHELL
 7 PIN OCTAL
 7AC

THE 6L6 AND 6L6G ARE DESIGNED WITH HIGH POWER SENSITIVITY AND HIGH EFFICIENCY FOR SERVICE IN THE OUTPUT STAGES OF AC RECEIVERS. THEY ARE CAPABLE OF DELIVERING AN OUTPUT AT ALL POWER LEVELS WITH A VERY LOW PERCENTAGE OF HARMONIC DISTORTION.

DIRECT INTERELECTRODE CAPACITANCES

	6L6	6L6G	
GRID TO PLATE	0.4	0.9	144 f
INPUT	10	11.5	144 f
OUTPUT	12	9.5	144 f

CONTINUED ON FOLLOWING PAGE

→ INDICATES A CHANGE OR ADDITION.

PRINTED IN U.S.A.

PLATE
 3025
 SEPT. 1
 1952

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS

INTERPRETED ACCORDING TO RMA STANDARD MB-210

	TRIODE ^A CONNECTION	PENTODE CONNECTION	
HEATER VOLTAGE	6.3	6.3	VOLTS
MAXIMUM HEATER CATHODE VOLTAGE	180	180	VOLTS
MAXIMUM PLATE VOLTAGE	275	360	VOLTS
MAXIMUM GRID #2 VOLTAGE	PLATE	270	VOLTS
MAXIMUM PLATE DISSIPATION	19	19	WATTS
MAXIMUM GRID #2 DISSIPATION	---	2.5	WATTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE			
FIXED BIAS OPERATION	0.1	0.1	MEGOHM
CATHODE BIAS OPERATION	0.5	0.5	MEGOHM

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A₁ AMPLIFIER - PENTODE CONNECTION

HEATER VOLTAGE	6.3	6.3	6.3	VOLTS
HEATER CURRENT	0.9	0.9	0.9	AMP.
PLATE VOLTAGE	250	300	350	VOLTS
GRID #2 VOLTAGE	250	200	250	VOLTS
GRID #1 VOLTAGE	-14	-12.5	-18	VOLTS
PEAK AF SIGNAL VOLTAGE	14	12.5	18	VOLTS
TRANSCONDUCTANCE	6 000	5 300	5 200	μMHOS
PLATE RESISTANCE	22 500	35 000	33 000	OHMS
ZERO SIGNAL PLATE CURRENT	72	48	54	MA.
MAXIMUM SIGNAL PLATE CURRENT	79	55	66	MA.
ZERO SIGNAL GRID #2 CURRENT	5	2.5	2.5	MA.
MAXIMUM SIGNAL GRID #2 CURRENT	7.3	4.7	7	MA.
LOAD RESISTANCE	2 500	4 500	4 200	OHMS
POWER OUTPUT	6.5	6.5	10.8	WATTS
TOTAL HARMONIC DISTORTION	10	11	15	PERCENT

CLASS A₁ AMPLIFIER - TRIODE CONNECTION^A

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.9	AMP.
PLATE VOLTAGE	250	VOLTS
GRID #2 VOLTAGE	PLATE	
GRID #1 VOLTAGE	-20	VOLTS
PEAK AF SIGNAL VOLTAGE	20	VOLTS
TRANSCONDUCTANCE	4 700	VOLTS
PLATE RESISTANCE	1 700	OHMS
AMPLIFICATION FACTOR	8	
ZERO SIGNAL PLATE CURRENT	40	MA.
MAXIMUM SIGNAL PLATE CURRENT	44	MA.
LOAD RESISTANCE	5 000	OHMS
POWER OUTPUT	1.4	WATTS
TOTAL HARMONIC DISTORTION	5	PERCENT

^A GRID #2 CONNECTED TO PLATE

CONTINUED ON FOLLOWING PAGE

→ INDICATES A CHANGE OR ADDITION.

PLATE
3026
SEPT. 1
1952

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

CLASS A₁ PUSH-PULL AMPLIFIER - PENTODE CONNECTION

VALUES ARE FOR TWO TUBES

HEATER VOLTAGE	6.3	6.3	VOLTS
HEATER CURRENT	0.9	0.9	AMP.
PLATE VOLTAGE	250	270	VOLTS
GRID #2 VOLTAGE	250	270	VOLTS
GRID #1 VOLTAGE	-16	-17.5	VOLTS
PEAK AF GRID TO GRID VOLTAGE	32	35	VOLTS
TRANSCONDUCTANCE (EACH TUBE)	5 500	5 700	UMHOS
PLATE RESISTANCE (EACH TUBE)	24 500	23 500	OHMS
ZERO SIGNAL PLATE CURRENT	120	134	MA.
MAXIMUM SIGNAL PLATE CURRENT	140	155	MA.
ZERO SIGNAL GRID #2 CURRENT	10	11	MA.
MAXIMUM SIGNAL GRID #2 CURRENT	16	17	MA.
LOAD RESISTANCE	5 000	5 000	OHMS
POWER OUTPUT	14.5	17.5	WATTS
TOTAL HARMONIC DISTORTION	2	2	PERCENT

CLASS AB₁ PUSH-PULL AMPLIFIER - PENTODE CONNECTION

VALUES ARE FOR TWO TUBES



HEATER VOLTAGE	6.3	6.3	VOLTS
HEATER CURRENT	0.9	0.9	AMP.
PLATE VOLTAGE	360	360	VOLTS
GRID #2 VOLTAGE	270	270	VOLTS
GRID #1 VOLTAGE	-22.5	-22.5	VOLTS
PEAK AF GRID TO GRID VOLTAGE	45	45	VOLTS
ZERO SIGNAL PLATE CURRENT	88	88	MA.
MAXIMUM SIGNAL PLATE CURRENT	132	140	MA.
ZERO SIGNAL GRID #2 CURRENT	5	5	MA.
MAXIMUM SIGNAL GRID #2 CURRENT	15	11	MA.
LOAD RESISTANCE	6 600	3 800	OHMS
POWER OUTPUT	26.5	18	WATTS
TOTAL HARMONIC DISTORTION	2	2	PERCENT



CLASS AB₂ PUSH-PULL AMPLIFIER - PENTODE CONNECTION

VALUES ARE FOR TWO TUBES

HEATER VOLTAGE	6.3	6.3	VOLTS
HEATER CURRENT	0.9	0.9	AMP.
PLATE VOLTAGE	360	360	VOLTS
GRID #2 VOLTAGE	225	270	VOLTS
GRID #1 VOLTAGE	-18	-22.5	VOLTS
PEAK AF GRID TO GRID VOLTAGE	52	72	VOLTS
ZERO SIGNAL PLATE CURRENT	78	88	MA.
MAXIMUM SIGNAL PLATE CURRENT	142	205	MA.
ZERO SIGNAL GRID #2 CURRENT	3.5	5	MA.
MAXIMUM SIGNAL GRID #2 CURRENT	11	16	MA.
LOAD RESISTANCE	6 000	3 800	OHMS
POWER OUTPUT	31	47	WATTS
TOTAL HARMONIC DISTORTION	2	2	PERCENT

6L6, 6L6G





PRINTED IN U. S. A.

PLATE
3029
SEPT. 1
1952

6L6, 6L6G

6L6, 6L6G
TRIODE CONNECTION
 $E_f = 6.3$ Volts




PLATE
3030
SEPT. 1
1952